



Wood Primer

AQUAGLO



INTERIOR & EXTERIOR



Halo Aquaglo Wood Primer, is a high bonding water-based formulation which ensures that the wood or masonry work is ready for a top coat of superior and lasting performance. It delivers high coverage at low VOC and low odour.

Experience, Wood Primer Aquaglo - *High Bonding water based primer for long paint life on wooden surfaces.*

PACK SIZES



1 L



4 L

GLOSS LEVEL



MATT



SILK



SATIN



GLOSS

FEATURES



High Bonding
Water Based
High Coverage

Quick Dry
Low Odour
Easy to apply
Low VOC

CAUTION



Do not apply below 10°C or above 45°C

Do not apply if humidity > 90%

Do not over-thin. Use thinned paint within 24 hours

Shake, stir and strain paint before use

Maintain air ventilation for quick drying

In case of eye contact, wash with plenty of water, seek medical attention

Tightly close the lid when not in use and store in a cool, dry place

CERTIFICATION



Compliant to VOC requirement for Paints for LEED rated buildings¹
Compliant to GRIHA standards for Low VOC²



PREPARATION

Wood:

- Ensure wood is aged properly. For pre-painted wood, scrape off loose paint
- Smoothen with emery paper no. 180. Remove any peeling paint and sand these areas to feather edges, smooth with adjacent surfaces. Wipe clean.
- Treat exposed knots with additional coat of Wood Primer

Masonry:

- Ensure leakage, seepage and efflorescence free surface
- Allow 28 days curing for painting freshly plastered surfaces
- Remove loose paint, dust/dirt particles and laitance with sand paper no. 180. Wipe clean
- Fix structural cracks, if any, with professional assistance
- Open non-structural cracks in V-groove and fill with cement/crack filler



APPLICATION

ROLLER DILUTION

For best results, use a brush & Short Nap Felt Roller as required
Dilute Wood Primer Aquaglo with up to 10% clean water (by volume)

Recommended System of Application

STEP	NO. OF COATS	PRODUCT	RECOAT TIME
STEP 1	1 COAT	 Wood Primer AQUAGLO (Upto 10% dilution)	4 hrs dry
STEP 2		Fill nail holes and dents on wood with wood filler/acrylic putty and on wall with cement/acrylic putty. Sand and smoothen with emery paper no. 180. Wipe clean.  Wall Putty ACRYLIC / CEMENT BASED	
STEP 3	Touch Up Coat	 Wood Primer AQUAGLO (Upto 10% dilution) Apply top coats after the above process.	4 hrs dry



INFORMATION AND CARE

ENVIRONMENTAL HEALTH AND SAFETY

- Use only with adequate ventilation during application and drying
- Avoid contact with eyes and prolonged or repeated contact with skin
- Do not breathe spray mist or sanding dust
- Use dust mask or nose pad during application, sanding and clean up
- Close container after each use
- Wash thoroughly after handling
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
- In case of skin contact, immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists
- No added Lead, Mercury, Chromium, Arsenic and other heavy metals

POST PAINTING CARE

- Apply finishing coat within 7 days of primer application

PRODUCT INFORMATION

Colours

White

KEY DATA

Coverage[^]

130 - 160 sq.ft./L/coats
12.1-14.8m²/L/coats

Drying Time*
(30°C @ 60%RH)

Surface Dry - 30 minutes
Recoat - 4 hours

Flash Point
Sheen Level

>200°C (Practically non-flammable)
2-5 units@60°H

Vehicle Type

Acrylic

Thin with

Clean Water

VOC levels~

<10 gms/L


Other JSW Paints Preparation Products:

JSW Paints Preparation Range offers an optimum base for the painting surface so as to ensure that the finishing coats provide a beautiful experience of painting spaces.

JSW Paints Top Coats Range:

Our extensive range of water-based top coats for metal and wood surfaces comes in gloss and satin finishes. Halo Aquaglo Majestic Satin is created to exude a rich-chic feel that works wonders when it comes to creating an ambience that emanates a feeling of elegance and understated opulence. Halo Aquaglo Majestic Gloss is carefully crafted for a glorious feel while creating a range of looks that are immaculate, impressive and truly beautiful.

JSW Paints - Think Beautiful. Every JSW Paints product works to transform beautiful thoughts into reality. Everything about the paint, its application and finish are designed to be the 'Simple-Swift-Sure' way of making homes beautiful.



METAL PRIMER
AQUAGLO



AQUAGLO
MAJESTIC GLOSS



AQUAGLO
MAJESTIC SATIN

¹Compliant to LEED (Leadership in Energy & Environmental Design) VOC criteria as per IGBC (Indian Green Building Council) as tested at National Test House, Mumbai. ²Compliant to GRIHA (Green Rating for Integrated Habitat Assessment) Criterion 26 on Low VOC Interior Paints as tested at National Test House, Mumbai.

Version No. 01 (04/2019.)

This information sheet supersedes all previous versions

For feedback/complaints, write to Customer Care Manager, JSW Paint Pvt. Ltd, Jindal Mansion, 5A, Dr. G.Deshmukh Marg, Mumbai 400 026, India or email at ccpaints@jsw.in or call on 1800-121-5797.

*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.

[^]Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.

~VOC Levels as certified by NTH. Meets VOC as per BIS Standard - IS 101 (Part 2/Sec 2)/1986 & IS 101 (Part 2/Sec 1)/1988