




Halõ Aquaglo

MAJESTIC GLOSS



INTERIOR & EXTERIOR



Halo Aquaglo Majestic Gloss, is designed to accentuate the smooth contours of your wood and metal surfaces in a wide range of colours. This odour less water based finish ensures a lasting glossy finish with resistance to fungus.

Experience, Halo Aquaglo Majestic Gloss - *Carefully crafted for a glorious finish.*

PACK SIZES



GLOSS LEVEL



FEATURES

- Germ Block
- Anti Bacterial
- Anti Fungal
- Gloss Lock
- Water Based
- Endures 5 years#
- Quick Dry
- Low Odour
- Easy to Apply
- Low VOC
- Breathable Coating

CAUTION

- Do not apply below 10°C or above 45°C
- Do not dilute above recommendation and use within 24 hrs post dilution
- Shake, stir and strain paint before use
- Maintain air ventilation for quick drying
- In case of eye contact, wash with water. Take medical advice
- Tightly close the lid when not in use. Store in a cool, dry place

CERTIFICATION

- Compliant to VOC requirement for Paints for LEED rated buildings¹
- Compliant to GRIHA standards for Low VOC²
- No Fungal Growth as per ASTM Test D5590:2017³
- Compliant to JIS test for Anti-Microbial Activity⁴



SURFACE PREPARATION

Wood:

- Ensure wood is aged properly. For pre-painted wood, scrape off loose paint
- Smoothen with emery paper no. 180. Wipe clean
- Treat exposed knots with additional coat of Wood Primer

Metal:

- Use appropriate method to ensure surface is free from dirt, oil, grease, rust or any contamination
- Remove loose rust and old loose paint by metal wire brushing
- Sand with sand paper no. 180 and wipe clean

Masonry:

- Ensure leakage, seepage and efflorescence free surface
- Allow 28 days curing for painting freshly plastered surfaces
- Remove loose paint, dust/dirt particles and laitance with sand paper no. 180. Wipe clean
- Fix structural cracks, if any, with professional assistance
- Open non-structural cracks in V-groove and fill with cement/crack filler



APPLICATION

- TOOLS** Brush & Short Nap Felt Roller as required
- DILUTION** 10% by volume with water for Top coat

Steps of Application – For Metal, Wood/Masonry Surface

STEP	NO. OF COATS	PRODUCT	RECOAT TIME
STEP 1	1 COAT	Wood Primer AQUAGLO (10% dilution) - For Wood Metal Primer AQUAGLO (5% dilution) - For Metal	4 hrs
STEP 2	As required On Wood/Masonry	Wall Putty ACRYLIC BASED	6-8 hrs
STEP 3	Sand and Smoothen with emery paper no. 180. Wipe Clean.		
STEP 4	Touch Up	Wood Primer AQUAGLO (10% dilution)	4 hrs
STEP 5	First Coat	Halõ Aquaglo MAJESTIC GLOSS	4 hrs
STEP 6	Second Coat**	Halõ Aquaglo MAJESTIC GLOSS	4 hrs

**Additional coats may be required for darker shades.



INFORMATION AND CARE

ENVIRONMENTAL HEALTH AND SAFETY

- Use only with adequate ventilation during application and drying
- Avoid contact with eyes and prolonged or repeated contact with skin
- Do not breathe spray mist or sanding dust
- Use dust mask or nose pad during application, sanding and clean up
- Close container after each use
- Wash thoroughly after handling
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
- In case of skin contact, immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists
- No added Lead, Mercury, Chromium, Arsenic and other heavy metals

POST PAINTING CARE

- Prevent sharp objects or impact that damage the paint film
- Ensure proper cleaning of the surface at an interval of 6 months

PRODUCT INFORMATION

Sheen Level	80 +/- 5 @ 60°GH
Tint Bases	QG-1, QG-3, QG-4, QG-Y, QG-M

KEY DATA

No. of colours	1800+
Direct Shades	White, Black, Smoke Grey, Golden Yellow, Lemon Yellow, Oxford Blue, Phirozi, Bus Green, Deep Orange, P.O.Red, Signal Red, Chilli Chocolate, Golden Brown
Coverage [^]	80 - 110 sq.ft./L/2 coats
Drying Time* (30°C @ 60°GH)	Surface Dry - 30 minutes Recoat - 4 hours
Flash Point	>200°C (Practically Non-flammable)
Vehicle Type	Acrylic
Thin with	Clean Water
VOC levels~	<10gms/L

Other Halõ products:

JSW Paints Halo Range offers best-in-class emulsions for Exterior and Interior Walls, eco-friendly water-based enamels - Aquaglo for Wood & Metal and Fresh range of fragrances for a beautiful experience of painting spaces.

Primers for Aquaglo: Metal Primer Aquaglo - First of its kind, rust-resistant water-based primer to guard metal surfaces. Wood Primer Aquaglo - High bonding water-based primer for long paint life on wooden surfaces.

Majestic Interior & Exterior Emulsions - a smooth, silken finish coupled with anti algal and weather protection properties create a beautiful long lasting look for the walls. Halo Aquaglo Majestic Satin is created to exude a rich-chic feel that works wonders when it comes to creating an ambience that emanates a feeling of elegance and understated opulence. The Halo Fresh range of fragrance additives lends a fresh, new feel that makes a home feel airy, beautiful and as good as new.

JSW Paints - Think Beautiful. Every JSW Paints product works to transform beautiful thoughts to reality. Everything about the paint, its application and finish is designed to be the 'Simple-Swift-Sure' way to making homes beautiful.



AQUAGLO WOOD PRIMER



AQUAGLO METAL PRIMER



MAJESTIC INTERIORS



MAJESTIC EXTERIORS



AQUAGLO MAJESTIC SATIN



FRESH MAJESTIC FRAGRANCES



JSW Paints presents Colourvista Shade Panorama, a splendid collection of 1808 curated shades assembled in tones for every mood. The Colourvista Shade Panorama Fandeck is uniquely designed to easily pick the right colour and choose colour combinations for homes.



Colourvista Shade Panorama

FEATURES OF THE INNOVATIVE FANDECK

- 1808 Curated Shades
- Tone Based User-friendly Fandeck
- Easy to Choose Colour Combinations

¹Compliant to LEED (Leadership in Energy & Environmental Design) VOC criteria as per IGBC (Indian Green Building Council) as tested at National Test House, Mumbai. ²Compliant to GRIHA (Green Rating for Integrated Habitat Assessment) Criterion 26 on Low VOC Interior Paints as tested at National Test House, Mumbai. ³No fungal growth when tested as per ASTM D5590: 2017 for 'Determining the Resistance of Paint Films to Fungal Defacement' as tested at Biotech Testing Services, Mumbai. ⁴Compliant to Japanese Industrial Standard - JIS Z 2801: 2010 'Test for Anti-Bacterial Activity and Efficacy' as tested at Biotech Testing Services, Mumbai.

Version No. 02(05/2022)

This information sheet supersedes all previous versions

For feedback/complaints, write to Customer Care Manager, JSW Paint Pvt. Ltd, Jindal Mansion, 5A, Dr. G.Deshmukh Marg, Mumbai 400 026, India or email at ccpaints@jsw.in or call on 1800-121-5797.

*Subject to compliance with conditions maintained in Product Information Sheet, regional climatic conditions, accidental damage, usual wear and tear in the area where applied.

*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.

[^]Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.

~VOC Levels as certified by NTH. Meets VOC as per BIS Standard - IS 101 (Part 2/Sec 2)/1986 & IS 101 (Part 2/Sec 1)/1988