



iBlok

WATERSTOP PRIME COAT



iBlok WaterStop Prime Coat Interiors is a waterproofing undercoat that protects your walls against moisture and surface dampness. Apply on interior wall surfaces to enhance the longevity of your top coat. For best results, use before painting with JSW Interior Emulsions.

Tested to protect walls from moisture and dampness.

PACK SIZES



GLOSS LEVEL



FEATURES

- Breathable Coating
- 10x better than normal Interior Primers
- Resist Negative Hydrostatic Pressure up to 2.5 bars
- High bonding
- Enhances the life of the top coat
- Increases coverage of the top coat

SURFACES

Plastered and prepared new masonry surfaces as well as prepared, previously painted interior walls

CERTIFICATION

Passes 2.5 bars resistance to Negative Hydrostatic Pressure as per ASTM D7088
Compliant to VOC requirement for paints for LEED rated buildings

CAUTION

Do not apply below 10 °C or above 45 °C
Do not apply if humidity > 90%
Do not over-thin. Use thinned paint within 24 hours
Shake, stir and strain paint before use
In case of eye contact, wash with plenty of water, seek medical attention
Tightly close the lid when not in use and store in a cool, dry place



PREPARATION

- Allow freshly plastered surfaces to cure for 28 days before painting
- Remove loose paint, dust, dirt, etc. with sandpaper no. 180 & wipe clean
- Study Structural cracks with structural engineer and repair
- Open non-structural cracks in V shaped grooves and fill with iBlok WaterStop Crack Fix
- Fill the dents with JSW Wall Putty – Cement Based / Acrylic Based as required & level the surface
- Sand with sandpaper no.180 & wipe clean



APPLICATION

- Apply i-Blok WaterStop Interior Primer with maximum of 50% dilution with water v/v using brush / roller with a forced coverage of 200 sqft/L
- Allow drying of 3-4 hours
- Apply appropriate finishing coat within 7 days

ROLLER

- For best results, use a Long Nap Felt Roller



INFORMATION AND CARE

ENVIRONMENTAL HEALTH AND SAFETY

- Use only with adequate ventilation during application and drying
- Avoid contact with eyes and prolonged or repeated contact with skin
- Do not breathe spray mist or sanding dust
- Use disposable rubber gloves, dust mask or nose pad during application, sanding and clean up
- Close container after each use
- Wash thoroughly after handling
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
- In case of skin contact, immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists
- No added Lead, Mercury, Chromium, Arsenic and other heavy metals

POST PAINTING CARE

- Apply finishing coat within 7 days of primer application



PRECAUTION

- Do not apply at temperatures below 10oC and over 45oC and humidity greater than 90%
- Ensure moisture content on the surface is below 40%
- Do not over-thin. Use thinned paint within 24 hours
- Shake, stir and strain before use
- Keep the room ventilated during the painting process
- In case of eye contact, wash with plenty of water. Take medical advice
- Tightly close the lid when not in use and store in a cool dry place

PRODUCT INFORMATION

Colours	White
Drying Time	• Surface Dry – 60 mins • Recoat – 4 hrs
Vehicle Type	Acrylic System
Thin with	Potable Water
VOC levels	Low VOC-

Other JSW Paints Preparation Products:

JSW Paints Preparation Range offers optimum base for the painting surface so as to ensure that the finishing coats provide a beautiful experience of painting spaces.



**iBLOK WATERSTOP
PRIME COAT EXTERIOR**



WALLPUTTY

JSW Paints Top Coats Range:

Our extensive range of water based emulsions are designed to capture myriad ideas of beauty and evoke a spectrum of emotions that set the perfect ambience.



HALO INTERIOR



AURUS INTERIOR



PIXIA INTERIOR

JSW Paints - Think Beautiful. Every JSW Paints product works to transform beautiful thoughts to reality. Everything about the paint, its application and finish is designed to be the 'Simple-Swift-Sure' way to making homes beautiful.

Version No. 01 (01/2021.)

This information sheet supersedes all previous versions

For feedback/complaints, write to Customer Care Manager, JSW Paint Pvt. Ltd, Jindal Mansion, 5A, Dr. G. Deshmukh Marg, Mumbai 400 026, India or email at ccpaints@jsw.in or call on 1800-121-5797.

*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.

^Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.

-VOC Levels as certified by NTH. Meets VOC as per BIS Standard – IS 101 (Part 2/Sec 2)/1986 & IS 101 (Part 2/Sec 1)/1988