



Wall Putty

ACRYLIC BASED
WHITE



JSW Wall Putty - Acrylic Based is a water based, ready to use putty which provides a strong and smooth foundation for a perfect paint finish. It is a technologically advanced product which has excellent filling and binding properties. It dries quick and leaves behind a super smooth surface ready for the application of top coat.

Experience JSW Wall Putty - Acrylic Based - Super Smooth Acrylic Putty with Strong Bonding

PACK SIZES



FEATURES



- Levelled and Smooth finish upon sanding
- Low dusting
- Strong bonding to substrate and subsequent coating
- Quick drying
- Easy application
- Superior crack filling
- Alkali Resistance
- Green Range - Low VOC, no added Lead or heavy metals

SURFACES



New or well prepared previously painted wall, plastered and prepared masonry surfaces

CAUTION



- Do not apply below 10 °C or above 45 °C
- Do not apply if humidity > 90%
- Do not over-thin. Use the thinned product within 24 hours
- In case of eye contact, wash with plenty of water, seek medical attention
- Tightly close the bag when not in use and store in a cool, dry place



PREPARATION

- Surfaces to be painted must be clean, dry and free from seepage, leakage, loose old paint, dirt, dust, grease, oil, soap, wax and any other contamination.
- Remove any peeling paint and sand these areas to feather edges smooth with adjacent surfaces
- New plaster or masonry surfaces must be allowed to cure (28 days) before application
- Cured plaster should be hard (non-powdery) and in sound condition
- Growths of fungus, algae or moss should be removed by wire brushing and washing thoroughly with potable water
- In case of areas having excess dampness/waterproofing issues, please repair the surface before painting
- In case of areas having excess dampness, please repair the surface before paint
- In case there are structural cracks, please study and repair them with a structural engineer
- Open non-structural cracks in V-groove and fill with cement/crack filler
- Apply acrylic putty (where needed) to fill the dents and level the surface as explained in the steps below
- Sand and smoothen the surface with sand paper no. 320 and wipe clean before paint application



APPLICATION

- ROLLER** For best results, use a quality putty knife
- DILUTION** Dilution not required - if required water can be added for consistency as per requirement

For new masonry surface^:

STEP 1	1 COAT	 Wall Primer INTERIORS	3-4 hrs dry
STEP 2	1 COAT	 Wall Putty ACRYLIC BASED	6-8 hrs dry before re-coat light sanding after drying with 180 mesh sand paper
STEP 3	1 COAT	 Wall Putty ACRYLIC BASED	6-8 hrs dry 6 to 8 hours drying, sanding after drying with 320 mesh sand paper
STEP 4	1 COAT	SANDING Sand and smoothen the surface with sand paper no. 320 and wipe clean before paint application	
STEP 5	1 COAT	 Wall Primer INTERIORS	3-4 hrs dry



INFORMATION AND CARE

ENVIRONMENTAL HEALTH AND SAFETY

- Use only with adequate ventilation during application and drying
- Avoid contact with eyes and prolonged or repeated contact with skin
- Do not breathe spray mist or sanding dust
- Use disposable rubber hand gloves, dust mask or nose pad during application, sanding and clean up
- Close bag after each use
- Wash thoroughly after handling
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
- In case of skin contact, immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists
- No added Lead, Mercury, Chromium, Arsenic or other heavy metals

POST PAINTING CARE

- Apply primer coat within 24-48 hrs of putty application
- Apply finishing coat within 7 days of primer application

PRODUCT INFORMATION

Colours

White

KEY DATA

Coverage[^]

40 - 60 sq.ft./kg
3.7 - 5.6 m²/L/coats

Drying Time*
(30°C @ 60 R/H)

Surface Dry - 30 minutes
Recoat - 4 hours

Flash Point

N/A

Sheen Level

N/A

Vehicle Type

Acrylic

Thin with

Clean Water if required

VOC levels~

<20 gms/kg

Other JSW Paints Preparation Products:

JSW Paints Preparation Range offers optimum base for the painting surface so as to ensure that the finishing coats provide a beautiful experience of painting spaces



INTERIOR PRIMER



EXTERIOR PRIMER



CEMENT PUTTY

JSW Paints Top Coats Range:

Our extensive range of water based emulsions are designed to capture myriad ideas of beauty and evoke a spectrum of emotions that set the perfect ambience.



HALO INTERIORS



AURUS INTERIORS



PIXA INTERIORS

JSW Paints - Think Beautiful. Every JSW Paints product works to transform beautiful thoughts to reality. Everything about the paint, its application and finish is designed to be the 'Simple-Swift-Sure' way to making homes beautiful.



Version No. 01 (04/2019.)

This information sheet supersedes all previous versions

For feedback/complaints, write to Customer Care Manager, JSW Paint Pvt. Ltd, Jindal Mansion, 5A, Dr. G.Deshmukh Marg, Mumbai 400 026, India or email at ccpaints@jsw.in or call on 1800-121-5797.

*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.

[^]Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.

~VOC Levels as certified by NTH. Meets VOC as per BIS Standard - IS 101 (Part 2/Sec 2)/1986 & IS 101 (Part 2/Sec 1)/1988