



Wall Putty

CEMENT BASED
WHITE



INTERIOR



EXTERIOR



JSW Wall Putty - Cement Based is a cement based premium quality putty which comes in powder form. With excellent filling and surfacing characteristics, strong bonding abilities and minimal dust, the putty is best suited to provide smooth aesthetic finish and extend the life of top coat paints. JSW Wall Putty - Cement Based is water resistant, has low VOC and is completely environmentally friendly.

Experience JSW Wall Putty - Cement Based - **Smooth and low dust cement putty**

PACK SIZES



1 KG



10 KG



40 KG

FEATURES



- Levelled and smooth finish upon sanding
- Low dusting
- Strong bonding to substrate and subsequent coating
- Quick drying
- Easy application
- Water-resistant
- Superior crack filling
- Alkali-Resistant
- Green Range - Low VOC, no added Lead or heavy metals

SURFACES



New or well prepared previously painted wall, plastered and prepared masonry surfaces

CAUTION



- Do not apply below 10 °C or above 45 °C
- Do not apply if humidity > 90%
- Do not over-thin. Use the diluted product within 24 hours
- In case of eye contact, wash with plenty of water, seek medical attention
- Tightly close the bag when not in use and store in a cool, dry place
- Once mixed with water, use within 40 - 45 min within the pot life, before setting



PREPARATION





- Surfaces to be painted must be clean, dry and free from seepage, leakage, loose old paint, dirt, dust, grease, oil, soap, wax and any other contamination.
- Remove any peeling paint and sand these areas to feather edges smooth with adjacent surfaces
- New plaster or masonry surfaces must be allowed to cure (28 days) before application
- Cured plaster should be hard (non-powdery) and in sound condition
- Growths of fungus, algae or moss should be removed by wire brushing and washing thoroughly with potable water
- In case of areas having excess dampness/waterproofing issues, please repair the surface before painting
- In case there are structural cracks, please study and repair them with a structural engineer
- Open non-structural cracks in V-groove and fill with cement/crack filler
- Apply cement (where needed) to fill the dents and level the surface as explained in the steps below
- Sand and smoothen the surface with sand paper no. 320 and wipe clean before paint application



APPLICATION

- ROLLER** For best results, use a quality putty knife
- DILUTION** 40% Water in 1 kg of cement putty

For new masonry surface^:

STEP 1	1 COAT	 Wall Primer INTERIORS/EXTERIORS	3-4 hrs dry
STEP 2	1 COAT	 Wall Putty CEMENT BASED	6-8 hrs dry before re-coat light sanding after drying with 180 mesh sand paper
STEP 3	1 COAT	 Wall Putty CEMENT BASED	6-8 hrs dry 6 to 8 hours drying, sanding after drying with 320 mesh sand paper
STEP 4	1 COAT	 Wall Primer INTERIORS/EXTERIORS	3-4 hrs dry



INFORMATION AND CARE

ENVIRONMENTAL HEALTH AND SAFETY

- Use only with adequate ventilation during application and drying
- Avoid contact with eyes and prolonged or repeated contact with skin
- Do not breathe spray mist or sanding dust
- Use disposable rubber hand gloves, dust mask or nose pad during application, sanding and clean up
- Use within 40 -45 min once mixed with water. Open bag needs to be used within 48 hrs.
- Wash thoroughly after handling
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
- In case of skin contact, immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists
- No added Lead, Mercury, Chromium, Arsenic or other heavy metals

POST PAINTING CARE

- Apply Primer within 24-48 hours of putty application
- Apply finishing coat within 7 days of primer application

PRODUCT INFORMATION

Colours

White

KEY DATA

Coverage[^]

10 - 20 sq.ft./kg for 2 coats
1.0 - 1.8 m²/kg/ 2 coats

Drying Time*
(30°C @ 60 R/H)

Surface Dry - 30 minutes
Recoat - 4 hours

Flash Point

N/A

Sheen Level

N/A

Binder Type

Cement and Polymer

Thin with

Clean Water, 40% in 1 kg

VOC levels~

<20 gms/kg

Other JSW Paints Preparation Products:

JSW Paints Preparation range offers optimum base for the painting surface so as to ensure that the finishing coats provide a beautiful experience of painting spaces.



INTERIOR PRIMER



EXTERIOR PRIMER



ACRYLIC WALL PUTTY

JSW Paints Top Coats Range:



Our extensive range of water-based emulsions are designed to capture myriad ideas of beauty and evoke a spectrum of emotions that set the perfect ambience.



HALO INTERIORS



AURUS INTERIORS



PIXIA INTERIORS

JSW Paints - Think Beautiful. Every JSW Paints product works to transform beautiful thoughts to reality. Everything about the paint, its application and finish is designed to be the 'Simple-Swift-Sure' way to making homes beautiful.

Version No. 01 (04/2019.)

This information sheet supersedes all previous versions

For feedback/complaints, write to Customer Care Manager, JSW Paint Pvt. Ltd, Jindal Mansion, 5A, Dr. G.Deshmukh Marg, Mumbai 400 026, India or email at ccpaints@jsw.in or call on 1800-121-5797.

*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.

[^]Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.

~VOC Levels as certified by NTH. Meets VOC as per BIS Standard - IS 101 (Part 2/Sec 2)/1986 & IS 101 (Part 2/Sec 1)/1988