



# Aur<sup>us</sup>

REGAL EXTERIORS

Tile Coat



EXTERIOR WALLS



Aurus Regal Exterior Tile Coat is a high-performing coating specially designed to protect roof tiles from extreme weather conditions. It is water-repellent, provides strong UV resistance, has a high sheen finish, and is available in a multitude of vibrant colours.

#### PACK SIZES



1 L



4 L



20 L

#### GLOSS LEVEL



MATT



SILK



SATIN



GLOSS

#### FEATURES



- Anti Algal
- Water Repellency
- High Sheen
- Low VOC
- Water Based
- Green Range

#### CAUTION

- Do not apply at temperatures below 10°C and over 45°C
- Do not over-thin. Use thinned paint within 24 hours
- Tightly close the lid when not in use and store in a cool, dry place
- Flaky, powdery substrate should not be painted directly
- Not recommended on glazed, non-porous, or very smooth tiles
- Do not apply on surfaces that are subject to seepage or leakage issues without arresting the water source
- Areas prone to algae growth will require an additional coat for better protection



#### CERTIFICATION



- Compliant to VOC requirement for Paints for LEED rated buildings<sup>1</sup>
- UV test results as per inhouse testing on QUV machine



## PREPARATION

- Ensure that the surface to be painted is free from any damp, loose paint, dust, oil, wax or grease and other contaminants
- Remove all contaminants such as dirt, grease, oil, dust, efflorescence, laitance, etc., with soap-powder solution using a Scrubbing Brush. Remove algae and fungus from affected area. Dry for a minimum of 4-6 hours before painting. Moisture content on the surface should be less than 16%
- Leaks and cracks causing constant dampness on roof tiles/surface should be corrected before painting
- Check random areas for adhesion of existing paint film in case of repainting. If problems are observed, total removal of old paint is required
- Tiles with surface imperfections such as holes, dents, and cracks are to be avoided. Use of any kind of putty is not recommended
- Use of any kind of primer is not recommended



## APPLICATION

- ROLLER** Apply with Long Nap Felt Roller or Brush as a priming coat
- DILUTION** Dilute Aurus Regal Exterior Top Coat with 25% potable water

For new masonry surface<sup>^</sup>:

STEP 1	1 COAT		4-6 hrs dry
STEP 2	2 COAT		4-6 hrs dry

For better hiding, third coat can be applied similarly  
Horizontal surfaces are painted with an additional coat for better protection



## INFORMATION AND CARE

#### ENVIRONMENTAL HEALTH AND SAFETY

- Use only with adequate ventilation during application and drying
- Avoid contact with eyes and prolonged or repeated contact with skin
- Do not breathe spray mist or sanding dust
- Use dust mask or nose pad during application, sanding and clean up
- Close container after each use
- Wash thoroughly after handling
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
- In case of skin contact, immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists
- No added Lead, Mercury, Chromium, Arsenic and other heavy metals

#### POST PAINTING CARE

- Prevent water stagnation and overgrowth of plants and trees near painted surface
- Prevent sharp objects or impact that damage paint film
- For best performance, ensure proper washing and cleaning of the painted surface at regular 6-month intervals. Do not wash the surface with a metal wire brush

## PRODUCT INFORMATION

Colours	White, Terra Power, Javelin Gold, Nadir
Tint Bases	AET-4

### KEY DATA

No. of colours	<b>19 shades</b> (Ask for Colourv <sup>ista</sup> Aurus Tile Coat and Floor Coat Shade Card)
Coverage <sup>^</sup>	<b>100-120 sq.ft./L/1 coat</b>
Drying Time* (30°C @ 60 R/H)	<b>Surface Dry - 6-8 hours</b> <b>Recoat - 4-6 hours</b>
Flash Point	<b>N/A</b>
Sheen Level	<b>25-30 units @ 60° GH</b>
Vehicle Type	<b>Acrylic</b>
Thin with	<b>Clean Water (upto 25%)</b>
VOC levels-	<b>&lt;80 gms/L</b>

## Other Au<sup>rus</sup> products:

The JSW Paints Aurus range features high-performing Regal Interior paints, Regal Exterior paints, Silk Interior paints, Silk Exterior paints, and Floor Coats. It's the perfect collection to choose from for a beautiful painting experience that you will thoroughly enjoy.

JSW Paints - Think Beautiful. Every JSW Paints product works to transform beautiful thoughts into reality. Everything about the paint, its application, and finish is designed to be the 'Simple-Swift-Sure' way to making homes beautiful.



REGAL INTERIORS



REGAL EXTERIORS



SILK INTERIORS



SILK EXTERIORS



FLOOR COAT EXTERIORS



INTERIOR & EXTERIOR



JSW Paints presents Colourv<sup>ista</sup> Shade Panorama, a splendid collection of 1808 curated shades assembled in tones for every mood. The Colourv<sup>ista</sup> Shade Panorama Fand<sup>ck</sup> is uniquely designed to easily pick the right colour and choose colour combinations for homes.



Colourv<sup>ista</sup> Shade Panorama

### FEATURES OF THE INNOVATIVE FANDECK

- 1808 Curated Shades
- Tone Based User-friendly Fand<sup>ck</sup>
- Easy to Choose Colour Combinations

<sup>1</sup>Compliant to LEED (Leadership in Energy & Environmental Design) VOC criteria as per IGBC (Indian Green Building Council) as tested at National Test House, Mumbai.

Version No. 01 (07/2022.)

This information sheet supersedes all previous versions

For feedback/complaints, write to Customer Care Manager, JSW Paint Pvt. Ltd, Jindal Mansion, 5A, Dr. G.Deshmukh Marg, Mumbai 400 026, India or email at ccpaints@jsw.in or call on 1800-121-5797.

\*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.

<sup>^</sup>Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.

-VOC Levels as certified by NTH. Meets VOC as per BIS Standard - IS 101 (Part 2/Sec 2)/1986 & IS 101 (Part 2/Sec 1)/1988