



Halö Exceed



JSW Paints Halo Exceed Long lasting Exteriors is formulated with 100% acrylic latex emulsion with Nanotechnology that provides 10X Protection to your Home Exteriors in all weather conditions for years. It is fibre-reinforced offering high mechanical strength, crack bridging and anti-carbonation properties. Its advanced Nano technology provides outstanding resistance to dirt pick-up.

Halo Exceed Long lasting Exteriors comes with 10 years Endurance, 7 years Waterproofing & 5 years Anti-Algal benefits.

TOPCOAT PACK SIZES



BASECOAT PACK SIZES



GLOSS LEVEL



FEATURES

- Low VOC
- Anti-Fungal
- Dust Resistant
- 10 Years Endurance & 7 Years Waterproofing
- 5 years Anti-Algal
- Crack Bridging Up To 2mm
- Reinforced With Fibres
- Colour Retention

CAUTION

- Do not apply at temperatures below 10°C or if temperature might drop to this level within 4hrs of application or above 45°C
- Do not apply if humidity > 90%
- Do not over-thin. Use thinned paint within 24 hours
- Shake, stir and strain paint before use
- In case of eye contact, wash with plenty of water
- Tightly close the lid when not in use and store in a cool, dry place
- Do not keep pails in direct sunlight
- Base Coat or only one coat of top coat should not be kept exposed in monsoon. Complete application before monsoon to be ensured
- Ensure to use potable water for dilution


CERTIFICATION

- Compliant to VOC requirement for Paints for LEED rated buildings¹
- Crack Bridging is carried out in accordance with EN- 1062 Part 7: 2004 - Method A²
- Anti Carbonation test carried out in accordance with EN- 1062 Part 6: 2002 - Method A³
- No Algal growth as per ASTM Test D5589-09 (2013)⁴
- Anti-fungal
- UV test results as per inhouse testing on QUV machine



SURFACE PREPARATION

- Surfaces to be painted must be clean, dry and free from seepage, leakage, loose old paint, dirt, dust, grease, oil, soap, wax and other impurities
- Remove any peeling paint and sand in these areas to feather edges smooth with adjacent surfaces
- Growth of fungus, algae or moss should be removed by wire brushing and wash thoroughly with potable water
- In case of areas having excess dampness, please repair the surface before painting
- Please arrest the source of water leakage or seepage in wall before application
- Do not apply the paint if moisture percentage is more than 15% in substrate
- Open non-structural cracks in V-groove and fill with cement/crack filler
- Wipe clean before paint application
- In case there are structural cracks, please study and repair them with a Structural Engineer
- New plaster or masonry surfaces must be allowed to cure for 28 days before application
- Cured plaster should be hard (non-powdery) and in sound condition
- Avoid application in rainy season
- In case of early rain after application and paint wash off, additional coat is recommended



APPLICATION

ROLLER: For best results, use a Long Nap Felt Roller

For Re-painting^ (Paint & Primer):

STEP	COATS	Product	Dry Time & Coverage
STEP 1	1 COAT	Halö Exceed BASECOAT	4 hrs dry before recoat Vertical & horizontal surfaces No dilution, coverage 30-35 sqft/L
STEP 2	2 COATS	Halö Exceed TOPCOAT	4 hrs dry before recoat Vertical surfaces only 25% dilution, coverage 50-55 sqft/L

Actual coverage may vary from the quoted coverage due to factors such as method, condition of application, surface roughness, and porosity. Please ensure you purchase the appropriate amount of product for the job.

For horizontal surfaces, one additional coat of Halo Exceed Topcoat is required

For New Masonry Surface^:

STEP	COATS	Product	Dry Time & Coverage
STEP 1	1 COAT	Halö Exceed BASECOAT	4 hrs dry before recoat Vertical & horizontal surfaces 25% dilution, coverage 50 sqft/L
STEP 2	1 COAT	Halö Exceed BASECOAT	4 hrs dry before recoat Vertical & horizontal surfaces No dilution, coverage 40-50 sqft/L
STEP 3	2 COATS	Halö Exceed TOPCOAT	4 hrs dry before recoat Vertical surfaces only 25% dilution, coverage 50-55 sqft/L for 2 coats

For horizontal surfaces, one additional coat of Halo Exceed Topcoat is required.



INFORMATION AND CARE

ENVIRONMENTAL HEALTH AND SAFETY

- Use only with adequate ventilation during application and drying
- Avoid contact with eyes and prolonged or repeated contact with skin
- Do not breathe spray mist or sanding dust
- Use dust mask or nose pad during application, sanding and clean up
- Close container after each use
- Wash thoroughly after handling
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
- In case of skin contact, immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists
- No added Lead, Mercury, Chromium, Arsenic and other heavy metals

POST PAINTING CARE

- Prevent water stagnation, overgrowth of plants and trees near the painted surface
- Prevent sharp objects or impact that damage the paint film
- Ensure proper cleaning of the surface at an interval of 6 months

PRODUCT INFORMATION

Colours	White
Tint Bases	HEE-1, HEE-2, HEE-3, HEE-4, HEE-M, HEE-Y

KEY DATA

No. of colours	1808 shades (Ask for Colourvista Shade Panorama fandeck)
Coverage[^]	50-55 sqft/L (Topcoat)
Drying Time* (30°C @ 60 R/H)	Surface Dry - 30 minutes Recoat - 4 hours
Flash Point	N/A
Sheen Level	3 - 16 units @ 60° GH
Vehicle Type	Acrylic
Thin with	Potable Water (upto 25%)
VOC levels~	<10gms/L

Other Halõ products:

JSW Paints Halo Range offers best-in-class emulsions for interior and exterior walls, eco-friendly water-based enamels - Aquaglo for Wood & Metal and fresh range of fragrances for a beautiful experience of painting spaces.

Carefully crafted for a glorious feel, Halo Aquaglo Majestic Gloss is designed to create a range of looks that are immaculate, impressive and truly beautiful. Halo Aquaglo Majestic Satin is created to exude a rich-chic feel that works wonders when it comes to creating an ambience that emanates a feeling of elegance and understated opulence. The Halo Fresh range of fragrance additives lends a fresh, new feel that makes a home feel airy, beautiful and as good as new.

JSW Paints - Think Beautiful. Every JSW Paints product works to transform beautiful thoughts to reality. Everything about the paint, its application and finish is designed to be the 'Simple-Swift-Sure' way to making homes beautiful.



MAJESTIC INTERIORS

MAJESTIC EXTERIORS



AQUAGLO MAJESTIC GLOSS

AQUAGLO MAJESTIC SATIN

FRESH MAJESTIC FRAGRANCES



JSW Paints presents Colourvista Shade Panorama, a splendid collection of 1808 curated shades assembled in tones for every mood. The Colourvista Shade Panorama Fandeck is uniquely designed to easily pick the right colour and choose colour combinations for homes.



Colourvista Shade Panorama

FEATURES OF THE INNOVATIVE FANDECK

- 1808 Curated Shades
- Tone Based User-friendly Fandeck
- Easy to Choose Colour Combinations

¹Compliant to LEED (Leadership in Energy & Environmental Design) VOC criteria as per IGBC (Indian Green Building Council) as tested at National Test House, Mumbai. ²Crack Bridging is carried out in accordance with EN- 1062 Part 7: 2004 - Method A. ³Anti Carbonation test carried out in accordance with EN- 1062 Part 6: 2002 - Method A. ⁴No Algal Growth when tested as per ASTM D5589-09 (2013) for determining the resistance of Paint Films to Algae Defacement as tested at Biotech Testing Services, Mumbai.

Version No. 01 (02/2022)

This information sheet supersedes all previous versions.

For feedback/complaints, write to Customer Care Manager at JSW Paints Pvt. Ltd., Jindal Mansion, 5A, Dr. G. Deshmukh Marg, Mumbai - 400026, India, or email at cpaints@jsw.in or call on 1800-121-5797

*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.

[^]Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.

~VOC Levels as certified by NTH. Meets VOC as per BIS Standard - IS 101 (Part 2/Sec 2)/1986 & IS 101 (Part 2/Sec 1)/1988