



Wall Putty

CEMENT BASED FRAGRANT PUTTY
WHITE



INTERIOR &
EXTERIOR

JSW Paints Wall Putty – Cement Based Fragrant Putty (Sandalwood) is a fine blend of high quality white cement, special polymers and fragrant additives. With its excellent filling and surfacing characteristics, the putty is best suited to provide a smooth finish to the walls. Due to strong bonding abilities, it extends the life of top coat paints.

The fragrance of sandalwood makes the construction site smell aromatic and refreshing thereby, it lowers stress, promotes calmness and helps in relaxation.

Experience JSW Paints Wall Putty - Cement Based Fragrant Putty (Sandalwood) - **Smooth and Sandalwood scented cement putty** that strengthens your walls.



Pack Size : 20 KG

FEATURES



FRAGRANT
BASED



SUPER
WHITE



ULTRA
SMOOTH



EASY
APPLICATION



LEVELLED AND
SMOOTH FINISH
UPON SANDING



LOW
DUSTING



STRONG BONDING
TO SUBSTRATE AND
SUBSEQUENT COATING



QUICK
DRYING



PREPARATION



- Surfaces to be painted must be clean, dry and free from seepage, leakage, loose old paint, dirt, dust, grease, oil, soap, wax and any other contamination
- Remove any loose paint and sand these areas to feather edges smooth with adjacent surfaces
- New plaster or masonry surfaces must be allowed to cure (28 days) before application
- Cured plaster should be hard (non-powdery) and in sound condition
- Growth of fungus, algae or moss should be removed by wire brushing and washing thoroughly with potable water
- In case of areas having excess dampness/waterproofing issues, please repair the surface before painting
- In case there are structural cracks, please study and repair them with a structural engineer
- Open non-structural cracks in V-groove and fill with cement/crack filler
- Apply cement (where needed) to fill the dents and level the surface as explained in the steps below
- Sand and smoothen the surface with sand paper no. 320 and wipe clean before paint application
- For repainting surfaces, Wall Primer application is needed before Wall Putty application



APPLICATION

- SUBSTRATE** New masonry surfaces or well prepared repainting surfaces
- TOOLS** For best results, use a quality putty knife
- DILUTION** 35%-40% potable water
- PRE-WET** Pre-wet the surface before application of 1st coat of Wall Putty

APPLICATION PROCESS

STEP 1	1 COAT	 Wall Primer INTERIORS/EXTERIORS	3-4 hrs drying
STEP 2	1 COAT	 Wall Putty CEMENT BASED FRAGRANT PUTTY	6-8 hrs drying before sanding with 320 mesh sand paper
STEP 3	1 COAT	 Wall Putty CEMENT BASED FRAGRANT PUTTY	6-8 hrs drying before sanding with 320 mesh sand paper
STEP 4	1 COAT	 Wall Primer INTERIORS/EXTERIORS	3-4 hrs drying



INFORMATION AND CARE

ENVIRONMENTAL HEALTH AND SAFETY

- Use only with adequate ventilation during application and drying
- Avoid contact with eyes and prolonged or repeated contact with skin
- Do not breathe spray mist or sanding dust
- Use disposable rubber hand gloves, dust mask or nose pad during application, sanding and clean up
- Wash thoroughly after handling
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
- In case of skin contact, immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists
- No added Lead, Mercury, Chromium, Arsenic or other heavy metals

PRECAUTION

- Do not apply below 10° C or above 45° C or if humidity is > 90%
- Pre-wet the surface before application of 1st coat and 2nd coat
- Do not sand the material vigorously as it may reduce the strength of putty film
- Do not apply if the substrate moisture content is more than 15%
- Arrest source of water incase of any water seepages or leakages
- Ensure the material is mixed homogeneously with water and allowed to stand for 5-10 mins before application
- Wall Putty once mixed with water should be used within 45 minutes
- Once the bag is opened, the material should be used within 48 hours
- Tightly close the bag when not in use and store in a cool, dry place
- Do not apply Wall Putty without pre-wetting the surface for the 1st coat

PRODUCT INFORMATION

Colour | White

KEY DATA

Coverage[^] <small>(for upto 1.5 mm thickness in 2 coats)</small>	10 - 15 sq.ft./kg/2 coats 0.9 - 1.4 m ² /kg/2 coats
Drying Time* <small>(30°C @ 60 R/H)</small>	Surface Dry - 1 hour Recoat - 6-8 hours
Flash Point	N/A
Sheen Level	N/A
Binder Type	Cement and Polymer
Thin with	Potable Water, 35% - 40% in 1 kg

POST PAINTING CARE

- Apply Primer within 24-48 hours of putty application
- Apply finishing coat within 7 days of primer application

Other JSW Paints Preparation Products:

JSW Paints Preparation Range offers an optimum base for the painting surface so as to ensure that the finishing coats provide a beautiful experience of painting spaces.



INTERIOR PRIMER



EXTERIOR PRIMER



CEMENT PUTTY



ACTYLIC PUTTY



JSW Texture

JSW Paints - Think Beautiful. Every JSW Paints product works to transform beautiful thoughts to reality. Everything about the paint, its application and finish are designed to be the 'Simple-Swift-Sure' way of making homes beautiful.

JSW Paints Top Coats Range:



Our extensive range of water-based emulsions are designed to capture myriad ideas of beauty and evoke a spectrum of emotions that set the perfect ambience.



HALO INTERIORS



PIXA INTERIORS



AURUS INTERIORS



HALO EXTERIORS



PIXA EXTERIORS



AURUS EXTERIORS



HALO SHINE EXTERIORS



PIXA SILK EXTERIORS



AURUS SILK EXTERIORS

Version No. 01 (09/2022).

For feedback/complaints, write to Customer Care Manager, JSW Paints Pvt. Ltd., Jindal Mansion, 5A, Dr. G. Deshmukh Marg, Mumbai 400 026, India or email at ccpaints@jsw.in or call on 1800-121-5797.

*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.

[^]Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.