



Aurus

REGAL EXTERIORS




EXTERIOR WALLS



Aurus Regal Exteriors Matt, is a hardwearing emulsion for exterior walls with a matt finish which has an advanced formulation protecting the paint against harmful sun rays. It helps prevent the paint from damage providing superior protection for your home against all types of extreme weather conditions, so your home can stay beautiful for longer.

Experience, Aurus Regal Exteriors Matt - *Thoughtfully designed for a UV Resistant Finish.*

PACK SIZES



1 L 4 L 10 L 20 L

GLOSS LEVEL

★ MATT ☆ SILK ☆ SATIN ☆ GLOSS

FEATURES	CAUTION	CERTIFICATION
<ul style="list-style-type: none"> Paint & Primer Low VOC UV Resistant Endures 5 Years <ul style="list-style-type: none"> Tough and Durable Film Maintains Colour Integrity Fast and Easy to Finish Roller Friendly Paint 	<ul style="list-style-type: none"> Do not apply below 10°C or above 45°C Do not apply if humidity > 90% Do not over-thin. Use thinned paint within 24 hours Shake, stir and strain paint before use In case of eye contact, wash with plenty of water Tightly close the lid when not in use and store in a cool, dry place 	<ul style="list-style-type: none"> Compliant to VOC requirement for Paints for LEED rated buildings¹ UV Block as per QUV Test²

PREPARATION

APPLICATION

- Surfaces to be painted must be clean, dry and free from seepage, leakage, loose old paint, dirt, dust, grease, oil, soap, wax and other impurities
- Remove any peeling paint and sand these areas to feather edges smooth with adjacent surfaces
- New plaster or masonry surfaces must be allowed to cure (28 days) before application
- Cured plaster should be hard (non-powdery) and in sound condition
- Growths of fungus, algae or moss should be removed by wire brushing and washing thoroughly with potable water
- In case of areas having excess dampness, please repair the surface before painting
- In case there are structural cracks, please study and repair them with a structural engineer
- Open non-structural cracks in V-groove and fill with cement/crack filler
- Apply cement putty (wherever needed) to fill the dents and level the surface
- Wipe clean before paint application

ROLLER For best results, use a Long Nap Felt Roller

DILUTION Dilute Aurus Regal Exteriors with 25% clean water

For re-painting^ (Paint & Primer):

STEP 1	FIRST COAT	 Aurus REGAL EXTERIORS	4 hrs dry
STEP 2	SECOND COAT	 Aurus REGAL EXTERIORS	4 hrs dry

For new masonry surface^:

STEP 1	1 COAT	 Wall Primer EXTERIORS	3-4 hrs dry
STEP 2	2 COAT	 Aurus REGAL EXTERIORS	4 hrs dry before re-coat

PAINT & PRIMER

Aurus Regal Exteriors is specially formulated to blend the functions of a primer with the finish coat. Two coats of Aurus Regal Exteriors provides a sturdier coat than the conventional 'Primer + 2 Finish coats' system, bringing your vision to life in quick time with less effort.*

*When painting unpainted surfaces, light shade over previous dark shade, painting over cement paint - a coat of JSW Exterior Wall Primer should be applied. Apply JSW Exterior Primer over spots where spot putty/cement/crack filler is applied. Allow primer to dry for 3-4 hours before finish coat.



INFORMATION AND CARE

ENVIRONMENTAL HEALTH AND SAFETY

- Use only with adequate ventilation during application and drying
- Avoid contact with eyes and prolonged or repeated contact with skin
- Do not breathe spray mist or sanding dust
- Use dust mask or nose pad during application, sanding and clean up
- Close container after each use
- Wash thoroughly after handling
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
- In case of skin contact, immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists
- No added Lead, Mercury, Chromium, Arsenic and other heavy metals

POST PAINTING CARE

- Prevent water stagnation, overgrowth of plants & trees near the painted surface.
- Prevent sharp objects or impact that damage the paint film
- Ensure proper cleaning of the surface at an interval of 6 months

PRODUCT INFORMATION

Colours	White
Tint Bases	AE-1, AE-2, AE-3, AE-4, AE-V, AE-M

KEY DATA

No. of colours	1808 shades (Ask for Colourvista Shade Panorama fandeck)
Coverage [^]	55 - 60 sq.ft./L/2 coats 5.1 - 5.6 m ² /L/2 coats
Drying Time* (30°C @ 60 R/H)	Surface Dry - 30 minutes Recoat - 4 hours
Flash Point	N/A
Sheen Level	5 - 8 units @ 60° GH
Vehicle Type	Acrylic
Thin with	Clean Water (upto 25%)
VOC levels~	<20 gms/L

Other Aurus products:

JSW Paints Aurus Range offers high performance emulsions for interior walls for a beautiful experience of painting spaces.

JSW Paints - Think Beautiful. Every JSW Paints product works to transform beautiful thoughts to reality. Everything about the paint, its application and finish is designed to be the 'Simple-Swift-Sure' way to making homes beautiful.



REGAL INTERIORS



JSW Paints presents Colourvista Shade Panorama, a splendid collection of 1808 curated shades assembled in tones for every mood. The Colourvista Shade Panorama Fandeck is uniquely designed to easily pick the right colour and choose colour combinations for homes.



Colourvista Shade Panorama

FEATURES OF THE INNOVATIVE FANDECK

- 1808 Curated Shades
- Tone Based User-friendly Fandeck
- Easy to Choose Colour Combinations

¹Compliant to LEED (Leadership in Energy & Environmental Design) VOC criteria as per IGBC (Indian Green Building Council) as tested at National Test House, Mumbai. ²Resistance to Ultra Violet Radiation as per ASTM D4587-11, when tested as per QUV exposure to ultra violet radiation for the duration of 1000 hours as per Internal Lab Test results.

Version No. 01 (04/2019.)

This information sheet supersedes all previous versions

For feedback/complaints, write to Customer Care Manager, JSW Paint Pvt. Ltd, Jindal Mansion, 5A, Dr. G.Deshmukh Marg, Mumbai 400 026, India or email at ccpaints@jsw.in or call on 1800-121-5797.

*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.

[^]Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.

~VOC Levels as certified by NTH. Meets VOC as per BIS Standard - IS 101 (Part 2/Sec 2)/1986 & IS 101 (Part 2/Sec 1)/1988