



# Halõ

MAJESTIC EXTERIORS



Halo Majestic Exteriors Silk, is an excellent emulsion for exterior walls with a silk finish which provides an active defense against algae, fungus, cracking, peeling and dirt pick up for exteriors, and provides the best-in-class weather resistance. So that your freshly painted exterior stays looking new even in extreme weather and sunlight year after year.

Experience Halo Majestic Exteriors Silk -  
*Carefully crafted for long-lasting protection.*

### PACK SIZES



### GLOSS LEVEL



### FEATURES

- Paint & Primer
- Low VOC
- Anti-Algal
- Anti-Fungal
- Dust Resistant
- Endures 7 Years
- Superior Opacity
- Excellent Colour Retention
- Fast and Easy to Finish
- Roller Friendly Paint

### CAUTION

- Do not apply below 10°C or above 45°C
- Do not apply if humidity > 90%
- Do not over-thin. Use thinned paint within 24 hours
- Shake, stir and strain paint before use
- In case of eye contact, wash with plenty of water
- Tightly close the lid when not in use and store in a cool, dry place

### CERTIFICATION

- Compliant to VOC requirement for Paints for LEED rated buildings<sup>1</sup>
- No Algal growth as per ASTM Test D5589-09 (2013)<sup>2</sup>
- UV Block as per QUV Test<sup>3</sup>



## PREPARATION

- Surfaces to be painted must be clean, dry and free from seepage, leakage, loose old paint, dirt, dust, grease, oil, soap, wax and other impurities
- Remove any peeling paint and sand these areas to feather edges smooth with adjacent surfaces
- New plaster or masonry surfaces must be allowed to cure for 28 days before application
- Cured plaster should be hard (non-powdery) and in sound condition
- Growths of fungus, algae or moss should be removed by wire brushing and wash thoroughly with potable water
- In case of areas having excess dampness, please repair the surface before painting
- In case there are structural cracks, please study and repair them with a Structural Engineer
- Open non-structural cracks in V-groove and fill with cement/crack filler
- Apply cement putty (wherever needed) to fill the dents and level the surface
- Wipe clean before paint application



## APPLICATION

- ROLLER** For best results, use a Long Nap Felt Roller
- DILUTION** Dilute Halo Majestic Exteriors Silk with 25% clean water

### For re-painting^ (Paint & Primer):

STEP 1	FIRST COAT	Halõ MAJESTIC EXTERIORS	4 hrs dry
STEP 2	SECOND COAT	Halõ MAJESTIC EXTERIORS	4 hrs dry

### For new masonry surface^:

STEP 1	1 COAT	Wall Primer EXTERIORS	3-4 hrs dry
STEP 2	2 COATS	Halõ MAJESTIC EXTERIORS	4 hrs dry before re-coat



## PAINT & PRIMER

Halo Majestic Exteriors is specially formulated to blend the functions of a primer with the finish coat. Two coats of Halo Majestic Exteriors provides a sturdier coat than the conventional 'Primer + 2 Finish coats' system, bringing your vision to life in quick time with less effort.\*

\*When painting unpainted surfaces, light shade over previous dark shade, painting over cement paint - a coat of JSW Exterior Wall Primer should be applied. Apply JSW Exterior Primer over spots where spot putty/cement/crack filler is applied. Allow primer to dry for 3-4 hours before finish coat.



## INFORMATION AND CARE

### ENVIRONMENTAL HEALTH AND SAFETY

- Use only with adequate ventilation during application and drying
- Avoid contact with eyes and prolonged or repeated contact with skin
- Do not breathe spray mist or sanding dust
- Use dust mask or nose pad during application, sanding and clean up
- Close container after each use
- Wash thoroughly after handling
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
- In case of skin contact, immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists
- No added Lead, Mercury, Chromium, Arsenic and other heavy metals

### POST PAINTING CARE

- Prevent water stagnation, overgrowth of plants and trees near the painted surface
- Prevent sharp objects or impact that damage the paint film
- Ensure proper cleaning of the surface at an interval of 6 months

## PRODUCT INFORMATION

<b>Colours</b>	<b>White</b>
<b>Tint Bases</b>	HE-1, HE-2, HE-3, HE-4, HE-V, HE-M

### KEY DATA

<b>No. of colours</b>	<b>1808 shades</b> (Ask for Colourv <sup>ista</sup> Shade <b>Panorama</b> fandeck)
<b>Coverage<sup>^</sup></b>	<b>60 - 65 sq.ft./2 coats</b> <b>5.5 - 6 sqm/2 coats</b>
<b>Drying Time* (30°C @ 60 R/H)</b>	<b>Surface Dry - 30 minutes</b> <b>Recoat - 4 hours</b>
<b>Flash Point</b>	<b>N/A</b>
<b>Sheen Level</b>	<b>12 - 15 units @ 60° GH</b>
<b>Vehicle Type</b>	<b>Acrylic</b>
<b>Thin with</b>	<b>Clean Water (upto 25%)</b>
<b>VOC levels~</b>	<b>&lt;10 gms/L</b>

## Other Halõ products:

JSW Paints Halo Range offers best-in-class emulsions for interior walls, eco-friendly water-based enamels - Aquaglo for Wood & Metal and fresh range of fragrances for a beautiful experience of painting spaces.

Carefully crafted for a glorious feel, Halo Aquaglo Majestic Gloss is designed to create a range of looks that are immaculate, impressive and truly beautiful. Halo Aquaglo Majestic Satin is created to exude a rich-chic feel that works wonders when it comes to creating an ambience that emanates a feeling of elegance and understated opulence. The Halo Fresh range of fragrance additives lends a fresh, new feel that makes a home feel airy, beautiful and as good as new.

JSW Paints - Think Beautiful. Every JSW Paints product works to transform beautiful thoughts to reality. Everything about the paint, its application and finish is designed to be the 'Simple-Swift-Sure' way to making homes beautiful.



JSW Paints presents Colourv<sup>ista</sup> Shade **Panorama**, a splendid collection of 1808 curated shades assembled in tones for every mood. The Colourv<sup>ista</sup> Shade **Panorama** Fandeck is uniquely designed to easily pick the right colour and choose colour combinations for homes.



Colourv<sup>ista</sup> Shade Panorama

### FEATURES OF THE INNOVATIVE FANDECK

- 1808 Curated Shades
- Tone Based User-friendly Fandeck
- Easy to Choose Colour Combinations

<sup>1</sup>Compliant to LEED (Leadership in Energy & Environmental Design) VOC criteria as per IGBC (Indian Green Building Council) as tested at National Test House, Mumbai. <sup>2</sup>No algal growth when tested as per ASTM D5589 -09 (2013) for Determining the resistance of Paint Films to Algae Defacement as tested at Biotech Testing Services, Mumbai. <sup>3</sup>Resistance to Ultra Violet Radiation when tested as per ASTM G155: 2013 of paint exposure to Ultra violet radiation generated by Xenon Arc for the duration of 1000 hours as tested at National Test House, Mumbai.

Version No. 01 (04/2019.)

This information sheet supersedes all previous versions

For feedback/complaints, write to Customer Care Manager, JSW Paint Pvt. Ltd, Jindal Mansion, 5A, Dr. G.Deshmukh Marg, Mumbai 400 026, India or email at ccpaints@jsw.in or call on 1800-121-5797.

\*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.

<sup>^</sup>Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.

~VOC Levels as certified by NTH. Meets VOC as per BIS Standard - IS 101 (Part 2/Sec 2)/1986 & IS 101 (Part 2/Sec 1)/1988