



# Aur<sup>us</sup>

REGAL INTERIORS  
Silk



INTERIOR WALLS



Aurus Regal Interiors Silk is a state-of-the-art emulsion for interior walls with Stain Block Technology and Silk Finish. This water-based 100% pure acrylic emulsion delivers excellent washability and stain resistance to bring the promise of long-lasting beauty alive. It also offers good elongation which resists formation of hairline cracks.

## PACK SIZES



## GLOSS LEVEL



## FEATURES

- Paint & Primer\*
- Endures 5 Years
- Stain Block
- Anti-fungal
- High Elongation
- Silk Finish
- Low VOC
- Superior Opacity

## SURFACES

New or previously painted walls, plaster, and prepared masonry surfaces.

## CERTIFICATION

- Crack Bridging of 430 microns as per EN 1062 Part 7:2004
- Compliant to VOC requirement for Paints for LEED rated buildings<sup>1</sup>
- Compliant to JIS test for Anti-Microbial Activity<sup>3</sup>
- No Fungal Growth as per ASTM Test D5590:20174

## CAUTION

- Do not apply at temperatures below 10°C or above 45°C
- Do not apply if humidity > 90%
- Do not over-thin. Use thinned paint within 24 hours
- Shake, stir and strain paint before use
- In case of eye contact, wash with plenty of water
- Tightly close the lid when not in use and store in a cool, dry place



## PREPARATION

- Surfaces to be painted must be clean, dry and free from seepage, leakage, loose old paint, dirt, dust, grease, oil, soap, wax and other impurities
- Remove any peeling paint and sand these areas to feather edges smooth with adjacent surfaces
- New plaster or masonry surfaces must be allowed to cure (28 days) before application
- Cured plaster should be hard (non-powdery) and in sound condition
- Growths of fungus, algae or moss should be removed by wire brushing and washing thoroughly with potable water
- In case of areas having excess dampness, please repair the surface before painting
- In case there are structural cracks, please study and repair them with a Structural Engineer
- Open non-structural cracks in V-groove and fill with cement/crack filler
- Apply cement/acrylic putty (where needed) to fill the dents and level the surface
- Sand and smoothen the surface with sandpaper no. 320 and wipe clean before paint application



## APPLICATION

**ROLLER** For best results, use a Short Nap Felt Roller  
**DILUTION** Dilute Aurus Regal Interiors Silk with 25% clean potable water

For re-painting<sup>^</sup> (Paint & Primer):

STEP 1	FIRST COAT	Aurus	4 hrs dry
STEP 2	SECOND COAT	Aurus	4 hrs dry

For new masonry surface<sup>^</sup>:

STEP 1	1 COAT	Wall Primer	3-4 hrs dry
STEP 2	2 COATS	Wall Putty	6-8 hrs dry
STEP 3	2 COATS	Aurus	4 hrs dry before re-coat



## PAINT & PRIMER

Aurus Regal Interiors Silk is specially formulated to blend the functions of a primer with the finish coat. Two coats of Aurus Regal Interiors Silk provides a sturdier coat than the conventional 'Primer + 2 Finish Coats' system, bringing your vision to life in quick time with less effort.\*

\*When painting unpainted surfaces, light shade over previous dark shade, painting over oil-based paint or distemper - a coat of JSW Interior Wall Primer should be applied. Where spot putty is done to prepare surface, apply JSW Interior Wall Primer over spots where putty is applied. Allow primer to dry for 3 to 4 hours before applying the finish coat on the wall.



## INFORMATION AND CARE

### ENVIRONMENTAL HEALTH AND SAFETY

- Use only with adequate ventilation during application and drying.
- Avoid contact with eyes and prolonged or repeated contact with skin.
- Do not breathe spray mist or sanding dust.
- Use dust mask or nose pad during application, sanding and clean up.
- Close container after each use.
- Wash thoroughly after handling.
- In case of contact with eyes, rinse your eyes immediately with plenty of water and seek medical advice.
- In case of skin contact, immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
- No added Lead, Mercury, Chromium, Arsenic and other heavy metals.

### POST PAINTING CARE

- Always remove any wall stains immediately from the walls
- Remove all dirt using a clean cloth or duster
- Always remove dirt from top to bottom. This helps in avoiding loose dirt smudging on the walls
- For household stains like pencil, tea, coffee, crayons, turmeric, ketchup, sketch pen, etc., use liquid dish wash/mild detergent solution. Use a sponge to remove the stains. Wipe the area with a clean cloth

## PRODUCT INFORMATION

Colours

Tint Bases

ASI Wht, ASI1, ASI3, ASI4, ASIY, ASIM

### KEY DATA

No. of colours

1808 shades  
(Ask for Colourvista Shade Panorama Fandeck)

Coverage^

100 - 120 sq.ft./L/2 coats

Drying Time\*  
(30°C @ 60 R/H)

Surface Dry - 30 minutes  
Recoat - 4 hours

Flash Point

N/A

Sheen Level

9 - 13

Vehicle Type

Acrylic

Thin with

Potable water

VOC levels~

<20 gms/L

## Other Aurus products:



JSW Paints Aurus Range offers fast & functional emulsions for Exterior and Interior walls. Aurus Joy provides smooth and bright finish for first time emulsion consumers who were using distemper and want to upgrade to emulsion.

JSW Paints - Think Beautiful. Every JSW Paints product works to transform beautiful thoughts to reality. Everything about the paint, its application, and finish is designed to be the 'Simple-Swift-Sure' way to making homes beautiful.



ELEGANT EXTERIORS



ELEGANT INTERIORS



JSW Paints presents Colourvista, a splendid collection of 1808 curated shades assembled in tones for every mood. The Colourvista Panorama Fandeck is uniquely designed to easily pick the right colour and choose colour combinations for homes.



Colourvista Shade Panorama

### FEATURES OF THE INNOVATIVE FANDECK

- 1808 Curated Shades
- Tone Based User-friendly Fandeck
- Easy to Choose Colour Combinations

Version No. 01 (01/2022.)

This information sheet supersedes all previous versions.

For feedback/complaints, write to Customer Care Manager at JSW Paints Pvt. Ltd., Jindal Mansion, 5A, Dr. G. Deshmukh Marg, Mumbai - 400 026, India or email at [ccpaints@jsw.in](mailto:ccpaints@jsw.in) or call on 1800-121-5797.

\*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.

^Actual coverage may vary from the quoted coverage due to factors such as method, condition of application, surface roughness and porosity.

~VOC Levels as certified by NTH. Meets VOC as per BIS Standard - IS 101 (Part 2/Sec 2)/1986 & IS 101 (Part 2/Sec 1)/1988