



Aurus

REGAL EXTERIORS
Flexxtra



Aurus Regal Exteriors Flexxtra is a high performance emulsion with a rich sheen, specially crafted for exteriors. It comes equipped with **FlexTech with Active NanoBonds** technology, which provides superior Crack-bridging ability and imparts excellent film strength, leading to enhanced durability. It provides strong resistance against algae, harsh weather and UV rays, thus keeping your homes beautiful for longer.

Experience Aurus Regal Exteriors Flexxtra - *"Thoughtfully designed for superior durability, weather protection and rich finish for your exteriors"*



FLEXTECH
WITH ACTIVE NANOBONDS

GLOSS LEVEL



MATT



SILK



SATIN



GLOSS

PACK SIZES



1 L



4 L



10 L



20 L

FEATURES

- Endures 6 years*
- Waterproofs 6 years*
- Excellent Crack-bridging ability
- Superior stretchability
- Anti-algal & Anti-fungal
- UV resistant
- Superior dust resistance
- Tough and durable film
- Anti-carbonation
- Paint & Primer*
- Low VOC
- Bright finish

CAUTION

- Do not apply below 10°C or above 45°C.
- Do not apply if humidity > 85%.
- Do not over-thin. Use thinned paint within 24 hours.
- Shake, stir, and strain paint before use.
- In case of eye contact, wash with plenty of water.
- Tightly close the lid when not in use and store in a cool, dry place.



CERTIFICATION



- Compliant to VOC requirement for paints for LEED rated buildings¹.
- No algal growth as per ASTM Test D5589: 2009².
- UV resistance as per ASTM Test G 154-2023.
- Crack-bridging is carried out in accordance with EN 1062-7(A)-2004 Test Method.
- Anti-carbonation test carried out in accordance with EN 1062-6-2002 Test Method
- No fungal growth as per ASTM Test D5590: 2017⁴.



PREPARATION

- Surfaces to be painted must be clean, dry and free from seepage, leakage, loose old paint, dirt, dust, grease, oil, soap, wax, and other impurities.
- Remove any peeling paint and sand these areas to feather the edges smooth with adjacent surfaces.
- New plaster or masonry surfaces must be allowed to cure for 28 days before application.
- Cured plaster should be hard (non-powdery) and in a sound condition.
- Growth of fungus, algae or moss should be removed by wire brushing and washing thoroughly with potable water.
- In case of areas having excess dampness, please repair the surface before painting.
- In case there are structural cracks, please study and repair them with a structural engineer.
- Open non-structural cracks in V-groove and fill with cement/crack filler.
- Apply cement putty wherever needed to fill the dents and level the surface.
- Wipe it clean before the paint application.



APPLICATION

ROLLER For best results, use a Long Nap Felt Roller.

DILUTION Dilute Aurus Regal Exteriors Flexxtra with 25% potable water.

For new masonry surface[^]:

STEP 1	1 COAT	Wall Primer EXTERIORS	3-4 hrs dry
STEP 2	2 COATS	Aurus REGAL EXTERIORS Flexxtra	4 hrs dry before recoat

For re-painting[^] (Paint & Primer):

STEP 1	FIRST COAT	Aurus REGAL EXTERIORS Flexxtra	4 hrs dry
STEP 2	SECOND COAT	Aurus REGAL EXTERIORS Flexxtra	4 hrs dry

For waterproofing application*:

STEP 1	2 COATS	iBlok WATERSTOP ROOF COAT OR WATERSTOP BASE COAT EXTERIORS	4 hrs dry before recoat
STEP 2	2 COATS	Aurus REGAL EXTERIORS Flexxtra	4 hrs dry

*For waterproofing application, please follow the iBlok waterproofing products application process and ensure coverage as recommended.



PAINT & PRIMER

Aurus Regal Exteriors Flexxtra is specially formulated to blend the functions of a primer with the finish coat. Two coats of Aurus Regal Exteriors Flexxtra provide a sturdier coat than the conventional 'Primer + 2 Finish coats' system, bringing your vision to life in quick time with less effort.*

*When painting unpainted surfaces, a light shade over a previous dark shade or painting over oil based paint or distemper - a coat of JSW Paints Wall Primer Exteriors/iBlok Base Coat Exteriors should be applied. In case of horizontal surfaces, additional coat is needed for better protection. Apply JSW Paints Exteriors Wall Primer / iBlok Base Coat Exteriors over spots where spot putty/cement/crack filler is applied. Allow primer to dry for 3-4 hours before the finish coat. **Additional coats may be required for darker shades with appropriate dilution of 15% vol./vol. with potable water for the Top Coat.



INFORMATION AND CARE

ENVIRONMENTAL HEALTH AND SAFETY

- Use only with adequate ventilation during application and drying.
- Avoid contact with eyes and prolonged or repeated contact with skin.
- Do not breathe spray mist or sanding dust.
- Use a dust mask or a nose pad during application, sanding and clean up.
- Close the container after each use.
- Wash thoroughly after handling.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact, immediately wash the affected area with a soap and plenty of water. Seek medical attention if irritation develops or persists.
- No added Lead, Mercury, Chromium, Arsenic, and other heavy metals.

POST PAINTING CARE

- Prevent water stagnation, overgrowth of plants, and trees near the painted surface.
- Prevent sharp objects or impacts that damage the paint film.
- Ensure proper cleaning of the surface at an interval of 6 months.

PRODUCT INFORMATION

Colours

White

Tint Bases

AEFX1, AEFX2, AEFX3, AEFX4, AEFXY, AEFXM

KEY DATA

No. of colours

1808 shades
(Ask for Colourvista Shade Panorama fandeck)

Coverage[^]

55 - 65 sq.ft./L/2coats
5.1 - 6 m²/L/2coats

Drying Time*

(30°C @ 60 R/H)

Surface Dry - 30 minutes

Recoat - 4 hours

Flash Point

N/A

Sheen Level

8 - 12 units @ 60° GH

Vehicle Type

Acrylic

Thin with

Potable Water (up to 25%)

VOC levels~

<20 gms/L

Other Aurus products:

JSW Paints Aurus Range offers high performance emulsions for interior and exterior walls, providing a beautiful experience of painting spaces.

JSW Paints - Think Beautiful. Every JSW Paints product works to transform beautiful thoughts to reality. Everything about the paint, its application and finish is designed to be the 'Simple-Swift-Sure' way to making homes beautiful.



REGAL INTERIORS SILK



REGAL INTERIORS



REGAL EXTERIORS



EXTERIOR



INTERIOR



REGAL EXTERIORS SILK



REGAL EXTERIORS TILE COAT



REGAL EXTERIORS FLOOR COAT



JSW Paints presents Colourvista Shade Panorama, a splendid collection of 1808 curated shades assembled in tones for every mood. The Colourvista Shade Panorama Fandeck is uniquely designed to easily pick the right colour and choose colour combinations for homes.



Colourvista Shade Panorama

FEATURES OF THE INNOVATIVE FANDECK

- 1808 curated shades.
- Tone-based user-friendly fandeck.
- Easy-to-choose colour combinations.

¹Compliant to LEED (Leadership in Energy & Environmental Design) VOC criteria as per IGBC (Indian Green Building Council) as tested at National Test House, Mumbai. ²No algal growth when tested as per ASTM D5589: 2009 for Determining the resistance of Paint Films to Algae Defacement as tested at Biotech Testing Services, Mumbai. ³Resistance to Ultra Violet Radiation when tested as per ASTM G154: 2023 of paint exposure to Ultra violet radiation for the duration of 500 hours as tested at GVM Test House, Mumbai. ⁴No fungal growth when tested as per ASTM 5590: 2017 for determining resistance of paint films to fungal defacement as tested at Biotech Testing Services, Mumbai.

Version No. 01 (11/2025).

This information sheet supersedes all previous versions, if any.

For feedback/complaints, write to Customer Care Manager, JSW Paints Limited, Jindal Mansion, 5A, Dr. G. Deshmukh Marg, Mumbai 400 026, India or email at ccpaints@jsw.in or call on 1800-121-5797.

*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.

^Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.

~VOC Levels as certified by NTH. Meets VOC as per BIS Standard - IS 101 (Part 2/Sec 2)/1986 & IS 101 (Part 2/Sec 1)/1988.