



iBlok

Waterstop Basecoat

DAMP SAFE

EXTERIORS



EXTERIOR WALLS



JSW Paints iBlok WaterStop Basecoat Damp Safe is designed to prevent moisture ingress and peeling, ideal for damp-prone walls for exterior surface which will boost the topcoat coverage and performance. Also will give the waterproofing warranty of 3 Years.

Tested to prevent wall dampness caused by water ingress through rain.

PACK SIZES



1 L

4 L

10 L

20 L

GLOSS LEVEL



MATT



SILK



SATIN



GLOSS

FEATURES

- 3 years waterproofing warranty*
- Superior Whiteness
- Fibre reinforcement
- Improves top coat performance
- Excellent adhesion
- Durability on exterior surfaces
- Suitable protective basecoat before topcoat
- Low VOC

SURFACES

- Plastered and prepared new masonry surfaces.
- Prepared previously painted exterior walls.
- Exterior wall areas requiring protection from water ingress through rain.



CAUTION

- Do not apply below 10°C or above 45°C.
- Do not apply if humidity is above 90%.
- Do not over-thin.
- Use diluted material within the recommended time.
- Shake, stir and strain before use.
- In case of eye contact, wash with plenty of water and seek medical attention.
- Tightly close lid when not in use.
- Store in a cool, dry place.



CERTIFICATION



As per (ASTM D 2370:2016) Tensile Strength of film is 2.76 N/mm²
As per (EN 12390-8:2019) it passes resistance to Positive Hydrostatic Pressure at 2 bars for verticals external surfaces.



PREPARATION

- Allow freshly plastered surfaces to cure for 28 days before painting.
- Remove loose paint, dust, dirt and other unstable material, then clean the surface thoroughly.
- For small cracks up to 3 mm, open the crack in a V-shaped groove and fill with the recommended crack-filling material.
- Repair other damaged areas as required before coating application.
- Fill dents and level the surface wherever required.
- Sand the surface and wipe it clean before application.



APPLICATION

- Allow new plaster to cure completely.
- Apply one coat of JSW Paints iBlok Damp Safe Exterior waterproofing primer after diluting 1 litre of product with 1 litre of water.
- Allow drying for 3-4 hours.
- Apply 2-3 coats of JSW Exterior Emulsion products as per the recommended.
- Dilution with water. Maintain a gap of 4-6 hours between consecutive coats.
- For horizontal surfaces such as window sills, edges, and other exposed areas. Apply one additional coat of topcoat to ensure enhanced protection



INFORMATION AND CARE

ENVIRONMENTAL HEALTH AND SAFETY

- Use only with adequate ventilation during application and drying.
- Avoid contact with eyes and prolonged or repeated contact with skin.
- Do not breathe spray mist or sanding dust.
- Use suitable protective gear such as gloves and mask during application and sanding.
- Wash thoroughly after handling.
- Close the container after each use.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of contact with skin, wash immediately with soap and water and seek attention if irritation persists.
- No added lead, mercury, chromium, arsenic and other heavy metals, if approved for claim use.

POST PAINTING CARE

- Apply finishing coat within the required time window.
- Clean the surface periodically for optimum performance.
- Do not apply under unsuitable temperature or humidity conditions.



PRECAUTION

- Do not apply at temperatures below 10°C and over 45°C and humidity greater than 90%.
- Ensure that the terrace surface has adequate slope to avoid water ponding.
- Ensure proper washing and cleaning of surface to avoid dust accumulation.
- Avoid actions like movement of heavy equipment or sharp objects on the terrace or anything which can puncture the coating.
- Tightly close the lid when not in use and store in a cool, dry place.

PRODUCT INFORMATION

Dilution	100%
Colours	White
Drying Time	• Surface Dry – 60 mins • Recoat – 4 hrs
Vehicle Type	Modified Acrylic System
Thin with	Potable Water
VOC levels	Low VOC-

Other JSW Paints Preparation Products:

JSW Paints Preparation Range offers optimum base for the painting surface so as to ensure that the finishing coats provide a beautiful experience of painting spaces.



IBLOK WATERSTOP
ROOF COAT EXTERIOR



IBLOK WATERSTOP
ROOF COAT MEGA
EXTERIORS



IBLOK WATERSTOP
BASE COAT INTERIORS



IBLOK WATERSTOP
BASE COAT EXTERIORS



IBLOK WATERSTOP
3K INTERIORS & EXTERIORS



IBLOK CRACK FIX
INTERIORS & EXTERIORS



IBLOK ROOF COAT
MEGA EXTERIORS

JSW Paints Top Coats Range:

Our extensive range of water-based emulsions are designed to capture myriad ideas of beauty and evoke a spectrum of emotions that set the perfect ambience.



HALO EXTERIOR



AURUS EXTERIOR



PIXA EXTERIOR

JSW Paints - Everything about the paint, its application and finish is designed to be the 'Simple-Swift-Sure' way to making homes beautiful.

Version No. 01. (July 2026)

This information sheet supersedes all previous versions.

For feedback/complaints, write to JSW Paints Ltd., Jindal Mansion, Dr. G. Deshmukh Marg, Mumbai 400 026, Maharashtra, India. or email at ccpaints@jsw.in or call on 1800-121-5797.

*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.

^Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.