



Pixa

ELEGANT INTERIORS
Silk



A uniquely developed water-based interior emulsion offering with more than 1808 shades, providing soft sheen along with high performance for a long time at an economical price. Its superior pigmentation gives the right amount of sheen and depth to the colour, adding character to the walls and making them look whiter and brighter.

Experience Pixa Elegant Interiors Silk - *Washable Acrylic Emulsion for smoother, brighter walls.*



GLOSS LEVEL



MATT



SILK



SATIN



GLOSS

PACK SIZES



FEATURES

Spreadmax- For Superior Coverage*
Paint & Primer*
Soft sheen
Whiter & brighter
Easy application
Superior opacity
4 years warranty*
Superior smoothness
Dullness Protection

SURFACES

New or previously painted wall, plaster and prepared masonry surfaces.
It is ideal for surfaces where good durability and superior coverage is desired with a bright finish.



CAUTION

Do not apply below 10°C or above 45°C.
Do not apply if humidity is more than 90%.
Do not over-thin. Use thinned paint within 24 hours.
Shake, stir and strain paint before use.
In case of contact with eyes, wash with plenty of water.
Tightly close the lid when not in use and store in a cool and dry place.



CERTIFICATION



Compliant to VOC requirement for Paints for LEED rated buildings¹.
Compliant to GRIHA standards for Low VOC².



PREPARATION

- Surfaces to be painted must be clean, dry and free from seepage, leakage, loose old paint, dirt, dust, grease, oil, soap, wax and other impurities.
- Remove any peeling paint and sand these areas to feather edges smooth with adjacent surfaces.
- New plaster or masonry surfaces must be allowed to cure (28 days) before application.
- Cured plaster should be hard (non-powdery) and in sound condition.
- Growths of fungus, algae or moss should be removed by wire brushing and washing thoroughly with potable water.
- In case of areas having excess dampness, please repair the surface before painting.
- In case there are structural cracks, please study and repair them with a structural engineer.
- Open non-structural cracks in a V-groove and fill with cement/crack filler.
- Apply cement/acrylic putty wherever needed to fill the dents and level the surface.
- Sand and smoothen the surface with sandpaper No. 320 and wipe it clean before paint application.



APPLICATION

ROLLER For best results, use a Short Nap Felt Roller.

DILUTION Dilute Pixa Elegant Interiors Silk with 50%-60% clean water.

For re-painting^ (Paint & Primer):

STEP 1	FIRST COAT	 Pixa ELEGANT INTERIORS SILK	4 hrs dry
STEP 2	SECOND COAT	 Pixa ELEGANT INTERIORS SILK	4 hrs dry

For new masonry surface^:

STEP 1	1 COAT	 Wall Primer INTERIORS	3-4 hrs dry
STEP 2	2 COATS	 Wall Putty ACRYLIC BASED	6-8 hrs dry
STEP 3	1 COAT	 Wall Primer INTERIORS	3-4 hrs dry
STEP 4	2 COATS	 Pixa ELEGANT INTERIORS	4 hrs dry before re-coat.



PAINT & PRIMER

Pixa Elegant Interiors Silk is specially formulated to blend the functions of a primer with the finish coat. Two coats of Pixa Elegant Interiors Silk provide a sturdier coat than the conventional 'Primer + 2 finish coats' system, bringing your vision to life in quick time with less effort.*

*When painting unpainted surfaces, light shade over previous dark shade or painting over oil based paint or distemper - a coat of JSW Interior Wall Primer should be applied. Where spot putty is done to prepare the surface, apply JSW Interior Wall Primer over spots where putty is applied. Allow primer to dry for 3 - 4 hours before applying the finish coat on the wall.



INFORMATION AND CARE

ENVIRONMENTAL HEALTH AND SAFETY

- Use only with adequate ventilation during application and drying.
- Avoid contact with eyes and prolonged or repeated contact with skin.
- Do not breathe spray mist or sanding dust.
- Use dust mask or nose pad during application, sanding and clean up.
- Close container after each use.
- Wash thoroughly after handling.
- In case of contact with eyes, rinse your eyes immediately with plenty of water and seek medical advice.
- In case of contact with skin, immediately wash skin with soap and plenty of water. Seek medical attention if irritation develops or persists.
- No added Lead, Mercury, Chromium, Arsenic and other heavy metals.

POST PAINTING CARE

- For best performance of paints, ensure proper washing and cleaning of all algal and fungal growth if any, at regular intervals of 6 months.

PRODUCT INFORMATION

Colours	Pristine White
Tint Bases	PSI 1, PSI 3, PSI 4, PSI V, PSI M

KEY DATA

No. of colours	1808 shades (Ask for Colourvista Shade Panorama Fandeck)
Coverage [^]	140 - 160 sq.ft./L/2 coats 13.00 - 14.86 m ² /L/2 coats
Drying Time* (30°C @ 60 R/H)	Surface Dry - 30 minutes Recoat - 4 hours
Flash Point	N/A
Sheen Level	5 - 9 units @ 60° GH
Vehicle Type	Acrylic
Thin with	Clean Water (50% - 60%)
VOC levels~	Low

Other PiXa Products:

JSW Paints PiXa Range offers fast and functional emulsions for Exterior and Interior Walls.

JSW Paints - Everything about the paint, its application and finish is designed to be the 'Simple-Swift-Sure' way to make homes beautiful.



PIXA ELEGANT INTERIORS



PIXA ELEGANT EXTERIORS SILK



PIXA ELEGANT EXTERIORS



JSW Paints presents Colourvista, a splendid collection of 1808 curated shades assembled in tones for every mood. The Colourvista Panorama Fandeck is uniquely designed to easily pick the right colour and choose colour combinations for every homes.



Colourvista Shade Panorama

FEATURES OF THE INNOVATIVE FANDECK

- 1808 Curated Shades
- Tone-based User-friendly Fandeck
- Easy to Choose Colour Combinations

¹Compliant to LEED (Leadership in Energy & Environmental Design) VOC criteria as per IGBC (Indian Green Building Council) as tested at National Test House, Mumbai. {Compliant to GRIHA (Green Rating for Integrated Habitat Assessment) Criterion 26 on Low VOC Interior Paints as tested at National Test House, Mumbai.

Version No. 02 (June 2026.)

This information sheet supersedes all previous versions

For feedback/complaints, write to JSW Paints Ltd., Jindal Mansion, Dr. G. Deshmukh Marg, Mumbai 400 026, Maharashtra, India. or email at ccpaints@jsw.in or call on 1800-121-5797.

*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.

[^]Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.