



iBlok

Waterstop Wall Putty

CEMENT BASED
WHITE



INTERIOR &
EXTERIOR



JSW Paints iBlok Waterstop Putty is a cement based premium quality putty which comes in powder form. With excellent Waterproofing ability, Anti-Efflorescence feature and strong bonding abilities, the putty is best suited to provide high smooth aesthetic finish & extended life of top coat paints.

iBlok Waterstop Putty is has low VOC and is completely environmentally friendly.



5 KG



40 KG

Pack Size :

FEATURES



- Water Repellent
- Efflorescence Resistance
- Levelled and Smooth finish upon sanding
- Low dusting
- Strong bonding to substrate and subsequent coating
- Quick drying
- Easy application
- Green Range – Low VOC, not added Lead and heavy metals

SURFACES



New or well prepared previously painted wall, plaster and prepared masonry surfaces

CAUTION



Do not apply at temperatures below 10°C or above 45°C

Do not apply if humidity > 90%

Do not over-dilute

In case of eye contact, wash with plenty of water, seek medical attention

Tightly close the bag when not in use and store in a cool, dry place

Once mixed with water, use within 40 - 45 min (at 30°C) within the pot life, before setting



PREPARATION

- Surfaces to be painted must be clean, dry and free from seepage, leakage, loose old paint, dirt, dust, grease, oil, soap, wax and any other contamination.
- Remove any peeling paint and sand these areas to feather edges smooth with adjacent surfaces
- New plaster or masonry surfaces must be allowed to cure (28 days) before application
- Cured plaster should be hard (non-powdery) and in sound condition
- Growths of fungus, algae or moss should be removed by wire brushing and washing thoroughly with potable water
- In case of areas having excess dampness/waterproofing issues, please repair the surface before painting
- In case there are structural cracks, please study and repair them with a structural engineer
- Open non-structural cracks in V-groove and fill with crack filler
- Apply cement (where needed) to fill the dents and level the surface
- It is not recommended to rub the final coat of putty with rough sand paper. It might break the water resistance properties. However, if needed level the surface with very fine not less than 500 water proof sand paper.



APPLICATION

TOOLS

For best results, use a good quality putty knife

DILUTION

35-40% Water in 1 kg of iBlok Waterstop Cement Putty

APPLICATION PROCESS

STEP 1	1 COAT		3-4 hrs drying
STEP 2	1 COAT		6-8 hrs drying After drying rub the surface gently with wet sponge or with putty blade in order to remove the loose particles.
STEP 3	2 COAT		Leave the surface to dry completely preferably for 24 hours. It is not recommended to rub the final coat of putty with rough sand paper.
STEP 4	1 COAT		3-4 hrs drying



INFORMATION AND CARE

ENVIRONMENTAL HEALTH AND SAFETY

- Use only with adequate ventilation during application and drying
- Avoid contact with eyes and prolonged or repeated contact with skin
- Do not breathe spray mist or sanding dust
- Use disposable rubber hand gloves, dust mask or nose pad during application, sanding and clean up
- Use within 40 -45 min once mixed with water. Open bag need to be used within 48 hrs.
- Wash thoroughly after handling
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
- In case of skin contact, immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists
- No added Lead, Mercury, Chromium, Arsenic and other heavy metals

POST PAINTING CARE

- Apply iBlok Waterstop Prime Coat Interiors within 24-48 hours of putty application
- Apply finishing coat within 7 days of iBlok Waterstop Prime Coat Interiors application

PRODUCT INFORMATION

Colour

White

KEY DATA

Coverage[^]

(for upto 1.5 mm thickness in 2 coats)

10 - 15 sq.ft./kg/2 coats

1 - 1.4 m²/kg/2 coats

Drying Time*

(30°C @ 60 R/H)

Surface Dry - 30 minutes

Recoat - 4-6 hours

Flash Point

N/A

Sheen Level

N/A

Binder Type

Cement and Polymer

Thin with

Clean Water, 40% in 1 kg

VOC Levels

N/A

Our iBlok range:

Our product range offers optimum base for the painting surface so as to ensure that the finishing coats provide a beautiful experience of painting spaces.



WATERSTOP PRIMECOAT
INTERIORS



CRACK FIX INTERIORS
& EXTERIORS



WATERSTOP PRIMECOAT
EXTERIORS



WATERSTOP ROOFCOAT
EXTERIORS

JSW Paints - Think Beautiful. Every JSW Paints product works to transform beautiful thoughts to reality. Everything about the paint, its application and finish are designed to be the 'Simple-Swift-Sure' way of making homes beautiful.

JSW Paints Top Coats Range:



Our extensive range of water-based emulsions are designed to capture myriad ideas of beauty and evoke a spectrum of emotions that set the perfect ambience.



HALÖ INTERIORS



PIXIA INTERIORS



AURUS INTERIORS



HALÖ EXTERIORS



PIXIA EXTERIORS



AURUS EXTERIORS



HALÖ SHINE
EXTERIORS



PIXIA SILK
EXTERIORS



AURUS SILK
EXTERIORS

Version No. 01 (03/2023).

This information sheet supersedes all previous versions

For feedback/complaints, write to Customer Care Manager, JSW Paints Pvt. Ltd., Jindal Mansion, 5A, Dr. G. Deshmukh Marg, Mumbai 400 026, India or email at ccpaints@jsw.in or call on 1800-121-5797.

*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.

[^]Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.