Halŏ

MAJESTIC INTERIORS

LuxGlo

JSW PAINTS

INTERIOR WALLS

JSW Paints Halo LuxGlo Interior paint delivers a premium Glo finish to your walls while keeping them protected. Now powered by Advanced Defense Technology, it eliminates 40+ germs, resists stains, and delivers up to 9 years of enduring brilliance.

Experience JSW Paints Halo Majestic Interiors Luxglo -
Let your walls Glo with Halo LuxGlo.

PACK SIZES

1 L | 4 L | 10 L | 20 L

GLOSS LEVEL

MATT | SILK | SATIN | **GLOSS**

FEATURES

- **Advanced Defense™ - Kills 40+ Germs***
- **Paint and primer**
- **Low VOC**
- **Excellent stain resistance**
- **Anti-fungal**
- **9 Years Warranty***
- Superior opacity
- Elegant sheen
- Excellent smooth finish
- Fast and easy to finish
- Roller friendly paint

CAUTION

- Do not apply below 10°C or above 45°C.
- Do not apply if humidity > 85%.
- Do not over-thin. Use thinned paint within 24 hours.
- Shake, stir and strain paint before use.
- In case of contact with eyes, wash with plenty of water.
- Tightly close the lid when not in use and store in a cool and dry place.

CERTIFICATION

- Compliant to VOC requirement for paints for LEED rated buildings[1].
- Compliant to GRIHA standards for Low VOC[2].
- Compliant to JIS test for anti-microbial activity[3].
- No fungal growth as per ASTM Test D5590:2017[4].
- Resistance to household stains as per ASTM Test D4828:94(2016)[5].

PREPARATION

- Surfaces to be painted must be clean, dry and free from seepage, leakage, loose old paint, dirt, dust, grease, oil, soap, wax and other impurities.
- Remove any peeling paint and sand these areas to feather edges smooth with adjacent surfaces.
- New plaster or masonry surfaces must be allowed to cure (28 days) before application.
- Cured plaster should be hard (non powdery) and in sound condition.
- Growths of fungus, algae or moss should be removed by wire brushing and wash thoroughly with potable water.
- In case of areas having excess dampness, please repair the surface before painting.
- In case there are structural cracks, please study and repair them with a structural engineer.
- Open non-structural cracks in a V-groove and fill with cement/crack filler.
- Apply cement/acrylic putty wherever needed to fill the dents and level the surface.
- Sand and smoothen the surface with sandpaper No. 320 and wipe it clean before paint application.
- Protection against efflorescence (white patches and flakes), if visible on the walls, needs to be done before application of the product.

APPLICATION

ROLLER For best results, use a Short Nap Felt Roller.
DILUTION Dilute Halo Majestic Interiors with 40-50% clean water.

For Repainting^:

STEP 1	FIRST COAT	Halŏ Majestic Interiors Basecoat / iBlok Waterstop Base Coat Interiors	3-4 hours dry.
STEP 2	2 COATS	Halŏ Majestic Interiors Luxglo	4 hours dry.

For New Masonry Surface^:

STEP 1	1 COAT	Wall Primer Interiors	3-4 hours dry.
STEP 2	2 COATS	Wall Putty Acrylic Based	6-8 hours dry before recoat.
STEP 3	1 COAT	Halŏ Majestic Interiors Basecoat / iBlok Waterstop Base Coat Interiors	3-4 hours dry.
STEP 4	2 COATS	Halŏ Majestic Interiors Luxglo	4 hours dry before recoat.

PAINT & PRIMER

Halo Majestic Interiors is specially formulated to blend the functions of a primer with the finish coat. Two** coats of Halo Majestic Interiors provide a sturdier coat than the conventional 'Primer + 2 Finish coats' system, bringing your vision to life in quick time with less effort.*

*When painting unpainted surfaces, light shade over previous dark shade, painting over oil based paint or distemper - a coat of JSW Interior Wall Primer should be applied. Apply JSW Interior Primer over spots where spot putty/cement/crack filler is applied. Allow primer to dry for 3 to 4 hours before finish coat. **Additional coats may be required for darker shades.
For Best results and availing warranty a coat of Halo Interior Basecoat needs to be applied. For waterproofing you can opt for IBlok Waterstop Basecoat.

INFORMATION AND CARE

ENVIRONMENTAL HEALTH AND SAFETY

- Use only with adequate ventilation during application and drying.
- Avoid contact with eyes and prolonged or repeated contact with skin.
- Do not breathe spray mist or sanding dust.
- Use dust mask or nose pad during application, sanding and clean up.
- Close container after each use.
- Wash thoroughly after handling.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of contact with skin, immediately wash skin with soap and plenty of water.
- Seek medical attention if irritation develops or persists.
- No added Lead, Mercury, Chromium, Arsenic and other heavy metals.

POST PAINTING CARE

- Always remove any wall stains immediately from the walls.
- Remove all dirt using a clean cloth or duster. Always remove dirt from top to bottom. This helps in avoiding loose dirt to smudge the walls.
- For household stains like pencil, tea, coffee, crayons, turmeric, ketchup, sketch pen etc., use liquid dish wash/mild detergent solution. Use a sponge to remove the stains. Wipe the area with a clean cloth.

PRODUCT INFORMATION

Colours	Pristine White
Tint Bases	HLI - PRSTN WHT, HLI-1, HLI-3, HLI-4, HLI-Y, HLI-M

KEY DATA

No. of colours	1840 shades (Ask for Colour*vista* Shade *Panorama* fandeck.)
Coverage^	140 - 160 sq.ft./L/2 coats 13 - 14.9 m^2/L/2 coats
Drying Time* (30°C @ 60 R/H)	Surface Dry - 30 minutes Recoat - 4 hours
Flash Point	N/A
Sheen Level	55 - 70 units @ 60° GH
Vehicle Type	Acrylic
Thin with	Clean Water (40%-50%) for lights shades, 15% - 20% for Dark shades
VOC levels~	<10gms/L

Other Halŏ products:

JSW Paints Halo Range offers best-in-class emulsions for Exterior Walls, eco-friendly water based enamels - Aquaglo for Wood & Metal and a fresh range of fragrances for a beautiful experience of painting spaces.

Carefully crafted for a glorious feel. The Halo Fresh range of fragrance additives lends a fresh, new feel that makes a home feel airy, beautiful and as good as new.

JSW Paints - Everything about the paint, its application and finish is designed to be the 'Simple-Swift-Sure' way to making homes beautiful.

INTERIOR EXTERIOR

MAJESTIC INTERIORS

MAJESTIC EXTERIORS

MAJESTIC EXTERIORS LUXGLO

EXCEED TOPCOAT

EXCEED BASECOAT

FRESH MAJESTIC FRAGRANCES

JSW PAINTS colour*vista*

JSW Paints presents Colour*vista* Shade ***Panorama****, a splendid collection of 1808 curated shades assembled in tones for every mood. The* Colour*vista* Shade ***Panorama*** *Fandeck is uniquely designed to easily pick the right colour and choose colour combinations for homes.*

Colour*vista* Shade **Panorama**

FEATURES OF THE INNOVATIVE FANDECK

- 1840 Curated Shades.
- Tone-based User-friendly Fandeck.
- Easy-to-choose Colour Combinations.

[1]Compliant to LEED (Leadership in Energy & Environmental Design) VOC criteria as per IGBC (Indian Green Building Council) as tested at National Test House, Mumbai. [2]Compliant to GRIHA (Green Rating for Integrated Habitat Assessment) Criterion 26 on Low VOC Interior Paints as tested at National Test House, Mumbai. [3]Compliant to Japanese Industrial Standard - JIS Z 2801: 2010 'Test for Anti-Bacterial Activity and Efficacy' as tested at Biotech Testing Services, Mumbai. [4]No fungal growth when tested as per ASTM D5590: 2017 for 'Determining the Resistance of Paint Films to Fungal Defacement' as tested at Biotech Testing Services, Mumbai. [5]Resistance to stains when tested as per ASTM D4828: 94 (2012) for relative ease of removal of common soil and stains from interior coatings as tested at National Test House, Mumbai.

Version No. 02 (06/2026.)
This information sheet supersedes all previous versions
For feedback/complaints, write to JSW Paints Ltd., Jindal Mansion, Dr. G. Deshmukh Marg, Mumbai 400 026, Maharashtra, India.
or email at ccpaints@jsw.in or call on 1800-121-5797.

*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.
^Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.
~VOC levels as certified by third party tests results. Meets VOC as per BIS Standard – IS 101 (Part 2/Sec 2)/1986 & IS 101 (Part 2/Sec 1)/1988.
*For 9 Years Warranty, priming to be done with Halo Interior Basecoat / iBlok Interior Basecoat.
*Basis test results conducted on Halo interior range of products by independent third-party laboratory as per ASTM, ISO & JIS standards. For further details please visit jswpaints.in