



Profect

REGAL INTERIORS



Profect Regal Interiors is a high-performance water based acrylic emulsion for interior walls with a rich matt finish. It provides superior performance, excellent hiding and best-in-class coverage.

Its unique formula enables colour to last longer. It is suitable for all normal interior masonry surfaces including particle board, fiber and insulation boards.

PACK SIZES



20 L

GLOSS LEVEL



MATT



SILK



SATIN



GLOSS

FEATURES



- Matt finish
- Anti-fungal
- Endures up to 5 years
- Superior opacity
- Excellent smooth finish
- Roller friendly paint

SURFACES



For new or previously painted walls, plastered and prepared masonry surfaces. Ideal for surfaces where good durability and superior coverage is desired with a bright finish.

CAUTION



- Do not apply below 10 °C or above 45 °C.
- Do not apply if humidity is greater than 90%.
- Do not over-thin. Use thinned paint within 24 hours.
- Shake, stir and strain the paint before use.
- In case of eye contact, wash with plenty of water.
- Tightly close the lid when not in use and store in a cool, dry place.



PREPARATION

- Surfaces to be painted must be clean, dry and free from seepage, leakage, loose old paint, dirt, dust, grease, oil, soap, wax and other impurities.
- Remove any peeling paint and sand these areas to feather edges smooth with adjacent surfaces.
- New plaster or masonry surfaces must be allowed to cure for 28 days before application.
- Cured plaster should be hard (non-powdery) and in sound condition.
- Growths of fungus, algae or moss should be removed by wire brushing, and washing thoroughly with potable water.
- In case of areas with excess dampness, please repair the surface before applying paint.
- In case there are structural cracks, please study and repair them with a structural engineer.
- Open non-structural cracks in a V-groove and fill with cement / crack filler. Prime the entire surface with Profect Primer Interior.
- Apply cement/acrylic putty (wherever needed) to fill the dents and level the surface.
- Sand and smoothen the surface with sandpaper no.320 and wipe clean before paint application.



APPLICATION

- Apply one coat of Profect Primer Interior over the entire surface.
- Allow primer to dry for 3-4 hours before applying the finish coat.
- Smoothen the surface with sandpaper no.320 and wipe it clean.
- Dilute paint with 40-50% potable water and apply two coats with Short Nap Felt Roller at an interval of 3-4 hours over properly prepared bare or painted interior surfaces.
- Dark shades may require additional finish coats.



INFORMATION AND CARE

HEALTH, SAFETY, SECURITY AND ENVIRONMENT

- Use only with adequate ventilation during application and drying.
- Avoid contact with eyes and prolonged or repeated contact with skin.
- Do not inhale the spray mist or sanding dust.
- Use a dust mask or nose pad during application, sanding and clean-up process.
- Close the container after each use and store in a cool and dry place, in an upright position.
- Keep out of reach of children and away from edible items.
- Do not use empty containers as means to store food.
- Seek immediate medical attention if paint is ingested or swallowed by mistake.
- Wash skin thoroughly after handling.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact, immediately wash with soap and plenty of water. Get medical attention if irritation develops or persists.
- Do not pour paint waste in water courses or in common waste. Needs to be recycled or disposed as per hazardous waste management rules.
- No added Lead, Mercury, Chromium, Arsenic or any other heavy metals.

POST PAINTING CARE

- Prevent sharp objects, or impact that may damage the paint film.
- Ensure proper cleaning of surface at an interval of every 6 months.

PRODUCT INFORMATION

Colours	White
Tint Bases	PRI 1

KEY DATA

No. of colours	927 shades (Ask for Colourvista Shade Panorama Fan deck)
Coverage^	110 - 120 sq.ft./L/2coats 10.2 - 11.14 m²/L/2coats
Drying Time* (30°C @ 60 R/H)	Surface Dry - 30 minutes Recoat - 4 hours
Flash Point	N/A
Sheen Level	2 - 5 units @ 60° GH
Vehicle Type	Acrylic
Thin with	Clean Water (upto 40 - 50%)
VOC levels~	Low

Other Prōfect Products:



ELEGANT INTERIORS



ELEGANT EXTERIORS



MAJESTIC EXTERIORS



REGAL EXTERIORS



JSW Paints presents Colourvista Shade Panorama, a splendid collection of 1808 curated shades assembled in tones for every mood. The Colourvista Shade Panorama Fandek enables you to easily pick the right colour and choose colour combinations for your projects.



Colourvista Shade Panorama

FEATURES OF THE INNOVATIVE FANDECK

- 1808 Curated Shades
- Tone Based User-friendly Fandek
- Easy to Choose Colour Combinations

Version No. 01 (07/2020.)

This information sheet supersedes all previous versions

For feedback/complaints, write to Customer Care Manager, JSW Paint Pvt. Ltd, Jindal Mansion, 5A, Dr. G.Deshmukh Marg, Mumbai - 400 026, India, or email at ccpaints@jsw.in or call on 1800-121-5797.

*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.

^Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.