JSW PAINTS

Profect

EXCEED EXTERIORS

EXTERIOR WALLS

JSW Paints Profect Exceed is a high performance, water-based acrylic emulsion with rich sheen for exterior surfaces. Its ClimaSeal technology protects the surface from all weather effects, acting as seal with the its DPUR, UV resistance, and Heat block properties. Its Advanced formula provides protection against water permeability, Algae and Carbon diffusion.

PACK SIZES



20 L

GLOSS LEVEL

MATT | **SILK** | SATIN | GLOSS

FEATURES

- **12 Year Warranty***
- **Heat Block**
- **Anti-Algal**
- **UV-Resistant**
- **Anti-Carbonation**
- **Crack Bridging**
- **Low VOC**
- **Colour Retention**
- **DPUR**

SURFACES

For new or previously painted walls, plastered and prepared masonry surfaces. Ideal for surfaces where good durability and superior coverage is desired with a bright finish.

CAUTION

- Do not apply below 10 °C or above 45 °C.
- Do not apply if humidity is more than 90%.
- Do not over-thin. Use thinned paint within 24 hours.
- Shake, stir and strain the paint before use.
- In case of contact with eye, wash with plenty of water.
- Tightly close the lid when not in use and store in a cool and dry place.

PREPARATION

- Surfaces to be painted must be clean, dry and free from seepage, leakage, loose old paint, dirt, dust, grease, oil, soap, wax and other impurities.
- Remove any peeling paint and sand these areas to feather the edges to blend smoothly with adjacent surfaces.
- New plaster or masonry surfaces must be allowed to cure for 28 days before application.
- Cured plaster should be hard (non-powdery) and in sound condition.
- Growths of fungus, algae or moss should be removed by wire brushing, and washing thoroughly with potable water.
- In case of areas with excess dampness, please repair the surface before applying paint.
- In case of structural cracks, please consult a Structural Engineer for assessment and repair.
- Open non-structural cracks in a V-groove and fill with cement/crack filler. Apply cement putty (wherever needed) to fill the dents and level the surface.
- Wipe it clean before paint application.

APPLICATION

ROLLER: For best results, use a Long Nap Felt Roller.

DILUTION 40%-50%.

For Waterproofing system:

STEP 1	AS PER BASECOAT SELECTION	Profect Waterstop Basecoat	4-6 hrs drying
STEP 2	2 COATS	Profect EXCEED EXTERIORS	4-6 hrs drying

For regular system:

STEP 1	1 COAT	Profect Wall Primer EXTERIORS	4-6 hrs drying
STEP 2	2 COATS	Profect EXCEED EXTERIORS	4-6 hrs drying

For Horizontal surfaces like chajjas, parapet tops, etc., additional coat is recommended. For dark shades dilution up to 15% vol./vol. with potable water is needed.

In case of regular system application, Primer is mandatory for Fresh Painting surface.

For any alternative coating systems, please contact the Sales representative.

INFORMATION AND CARE

ENVIRONMENTAL HEALTH AND SAFTEY

- Use only with adequate ventilation during application and drying.
- Avoid contact with eyes and prolonged or repeated contact with skin.
- Do not inhale the spray mist or sanding dust.
- Use a dust mask or nose pad during application, sanding and clean-up process.
- Close the container after each use and store in a cool and dry place, in an upright position.
- Keep out of reach of children and away from food items.
- Do not use empty containers as means to store food.
- Seek immediate medical attention if paint is ingested or swallowed by mistake.
- Wash skin thoroughly after handling.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of contact with skin, immediately wash with soap and plenty of water. Seek medical attention if irritation develops or persists.
- Do not pour paint waste in watercourses or in common waste. Needs to be recycled or disposed as per hazardous waste management rules.
- No added Lead, Mercury, Chromium, Arsenic or any other heavy metals.

POST-PAINTING CARE

- Prevent water stagnation, overgrowth of plants & trees near the painted surface.
- Prevent sharp objects or impact that may damage the paint film.
- Ensure proper cleaning of the surface every 6 months.

PRODUCT INFORMATION

Colours	**White**
Tint Bases	**PEXE 1, 2, 4**

KEY DATA

No. of colours	**1200+ shades** (Ask for Colour***vista*** Shade ***Panorama*** fan deck)
Coverage^	**55 - 65 sq.ft./L/2coats** **5.11 – 6.03 m²/L/2coats**
Drying Time* (30°C @ 60 R/H)	**Surface Dry - 30 minutes** **Recoat - 4 hours**
Flash Point	**N/A**
Sheen Level	**20–26 units @ 60° GH**
Vehicle Type	**Modified Acrylic**
Thin with	**Clean Water (40%-50%)**
VOC levels~	**15-45 gms/L**

Other Profect Range:

INTERIOR & EXTERIOR



PROFECT EXCEED MEGA EXTERIOR



PROFECT EXCEED EXTERIOR



PROFECT MAJESTIC EXTERIOR SILK

JSW PAINTS colourvista

JSW Paints presents Colour***vista*** Shade ***Panorama****, a splendid collection of 1808 curated shades assembled in tones for every mood. The* Colour***vista*** Shade ***Panorama*** *Fandeck enables you to easily pick the right colour and choose colour combinations for your projects.*



Colour***vista*** Shade **Panorama**

FEATURES OF THE INNOVATIVE FANDECK

- 1808 Curated Shades
- Tone Based User-friendly Fan deck
- Easy to Choose Colour Combinations

Version No. 01 (08/2026)
This information sheet supersedes all previous versions
For feedback/complaints, write to Customer Care Manager, JSW Paint Ltd, Jindal Mansion, 5A, Dr. G.Deshmukh Marg, Mumbai - 400 026, India, or email at ccpaints@jsw.in or call on 1800-121-5797.

*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.
^Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.