JSW PAINTS

# Profect

LONG LASTING EXTERIORS

EXTERIOR WALLS

JSW Paints Profect Longlasting Exteriors is a high-performance, water-based acrylic emulsion with rich sheen for exterior surfaces. It provides long lasting protection to the surface against challenging weather effects. The TriGuard Tech forms a bio-shield to protect against Algae & fungus, Anti-Carbonation guard against carbon diffusion, dirt block to keep the walls elegant.

**PACK SIZES**




20 L

**GLOSS LEVEL**

MATT | **SILK** | SATIN | GLOSS

## FEATURES

- 10 Year Warranty*
- Heat Block upto 5° C
- Anti-Algal
- UV-Resistant
- Anti-Carbonation
- Low VOC
- Colour Retention
- DPUR

## SURFACES

For new or previously painted walls, plastered and prepared masonry surfaces. Ideal for surfaces where good durability and superior coverage is desired with a bright finish.

## CAUTION

- Do not apply below 10 °C or above 45 °C.
- Do not apply if humidity is more than 90%.
- Do not over-thin. Use thinned paint within 24 hours.
- Shake, stir and strain the paint before use.
- In case of contact with eye, wash with plenty of water.
- Tightly close the lid when not in use and store in a cool and dry place.

## PREPARATION

- Surfaces to be painted must be clean, dry and free from seepage, leakage, loose old paint, dirt, dust, grease, oil, soap, wax and other impurities.
- Remove any peeling paint and sand these areas to feather the edges to blend smoothly with adjacent surfaces.
- New plaster or masonry surfaces must be allowed to cure for 28 days before application.
- Cured plaster should be hard (non-powdery) and in sound condition.
- Growths of fungus, algae or moss should be removed by wire brushing, and washing thoroughly with potable water.
- In case of areas with excess dampness, please repair the surface before applying paint.
- In case of structural cracks, please consult a Structural Engineer for assessment and repair.
- Open non-structural cracks in a V-groove and fill with cement/crack filler. Apply cement putty (wherever needed) to fill the dents and level the surface.
- Wipe it clean before paint application.

## APPLICATION

**ROLLER:** For best results, use a Long Nap Felt Roller.

**DILUTION** 40%-50%.

**For Waterproofing system:**

| | | | |
|---|---|---|---|
| STEP 1 | AS PER PIS | Profect Waterproofing Basecoat | 4-6 hrs drying |
| STEP 2 | 2 COAT | Profect LONG LASTING EXTERIORS | 4-6 hrs drying |

**For regular system:**

| | | | |
|---|---|---|---|
| STEP 1 | 1 COAT | Profect Wall Primer EXTERIORS | 4 hrs drying |
| STEP 2 | 2 COAT | Profect LONG LASTING EXTERIORS | 4 hrs drying |

For Horizontal surfaces like chajjas, parapet tops, etc., additional coat is recommended. For dark shades dilution up to 15% vol./vol. with potable water is needed.

In case of regular system application, Primer is mandatory for Fresh Painting surface.

For any alternative coating systems, please contact the Sales representative.

## INFORMATION AND CARE

### ENVIRONMENTAL HEALTH AND SAFETY

- Use only with adequate ventilation during application and drying.
- Avoid contact with eyes and prolonged or repeated contact with skin.
- Do not inhale the spray mist or sanding dust.
- Use a dust mask or nose pad during application, sanding and clean-up process.
- Close the container after each use and store in a cool and dry place, in an upright position.
- Keep out of reach of children and away from food items.
- Do not use empty containers as means to store food.
- Seek immediate medical attention if paint is ingested or swallowed by mistake.
- Wash skin thoroughly after handling.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of contact with skin, immediately wash with soap and plenty of water. Seek medical attention if irritation develops or persists.
- Do not pour paint waste in watercourses or in common waste. Needs to be recycled or disposed as per hazardous waste management rules.
- No added Lead, Mercury, Chromium, Arsenic or any other heavy metals.

### POST-PAINTING CARE

- Prevent water stagnation, overgrowth of plants & trees near the painted surface.
- Prevent sharp objects or impact that may damage the paint film.
- Ensure proper cleaning of the surface every 6 months.

## PRODUCT INFORMATION

| | |
|---|---|
| **Colours** | **White** |
| **Tint Bases** | **PLE 1, 2, 4** |

### KEY DATA

| | |
|---|---|
| **No. of colours** | **1400+ shades** (Ask for Colour***vista*** Shade ***Panorama*** fan deck) |
| **Coverage^** | **55 - 65 sq.ft./L/2coats**<br>**5.11 – 6.03 m²/L/2coats** |
| **Drying Time* (30°C @ 60 R/H)** | **Surface Dry - 30 minutes**<br>**Recoat - 4 hours** |
| **Flash Point** | **N/A** |
| **Sheen Level** | **20–26 units @ 60° GH** |
| **Vehicle Type** | **Modified Acrylic** |
| **Thin with** | **Clean Water (30%-40%)** |
| **VOC levels~** | **15-45 gms/L** |

## Other Profect Range:

INTERIOR & EXTERIOR




**PROFECT EXCEED MEGA EXTERIOR**




**PROFECT EXCEED EXTERIOR**




**PROFECT MAJESTIC EXTERIOR SILK**

JSW PAINTS colourvista

*JSW Paints presents* Colour***vista*** Shade ***Panorama****, a splendid collection of 1808 curated shades assembled in tones for every mood. The* Colour***vista*** Shade ***Panorama*** *Fandeck enables you to easily pick the right colour and choose colour combinations for your projects.*



Colour***vista*** Shade **Panorama**

### FEATURES OF THE INNOVATIVE FANDECK

- 1808 Curated Shades
- Tone Based User-friendly Fan deck
- Easy to Choose Colour Combinations

Version No. 01 (08/2026)
This information sheet supersedes all previous versions
For feedback/complaints, write to Customer Care Manager, JSW Paint Ltd, Jindal Mansion, 5A, Dr. G.Deshmukh Marg, Mumbai - 400 026, India, or email at ccpaints@jsw.in or call on 1800-121-5797.

*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.
^Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.