Profect Waterstop Base coat EXTERIORS

JSW PAINTS

EXTERIOR WALLS

JSW Paints Profect WaterStop Basecoat Exteriors is a waterproofing base coat that can be applied on Vertical walls and Parapet walls. It can also be applied on horizontal surfaces like roof/facades. It acts as a perfect waterproofing base coat for all JSW Exterior Emulsions. The Profect WaterStop BaseCoat Exteriors comes as a unique product owing to its high water resistance and ability to withstand high water pressure.

PACK SIZES



20 L

GLOSS LEVEL

★ MATT ☆ SILK ☆ SATIN ☆ GLOSS

FEATURES

- Crack Bridging
- Anti-Efflorescence
- Waterproofs 5 years
- Resists Positive Hydrostatic Pressure up to 4 bars on vertical surfaces
- Resists Positive Hydrostatic Pressure up to 6 bars on horizontal surfaces
- Low VOC
- Excellent adhesion
- High Flexibility

SURFACES

For new or previously painted walls, plastered and prepared masonry surfaces. Ideal for surfaces where good durability and superior coverage is desired with a bright finish.

CAUTION

- Do not apply below 10 °C or above 45 °C.
- Do not apply if humidity is more than 90%.
- Do not over-thin. Use thinned paint within 24 hours.
- Shake, stir and strain the paint before use.
- In case of contact with eye, wash with plenty of water.
- Tightly close the lid when not in use and store in a cool and dry place.

PREPARATION

- Allow freshly plastered surfaces to cure for 28 days before painting.
- Remove all loose paint, fungus and algae with wire brush and thoroughly clean with water.
- Study structural cracks with structural engineer and repair.
- Open non-structural cracks in a V shaped grooves and fill with JSW Paints i-Blok WaterStop Crack Fix.

APPLICATION

Horizontal surfaces:

Apply self-priming coat (diluted with water 25% v/v) using brush/roller at forced coverage of 75 sqft/l. Apply 2 coats without dilution using brush/roller at forced coverage of 37 sqft/l for each coat to achieve overall coverage of 15 sqft/l.

Ensure that Profect Waterstop Basecoat Exteriors is applied over the entire roof and parapet walls to form a continuous blanket.

Vertical surfaces:

Apply self-priming coat (diluted with water 25% v/v) using brush/roller at forced coverage of 90 sqft/l. Apply one additional coat without dilution using brush/roller at forced coverage of 90 sqft/l to achieve overall coverage of 45 sqft/l. Allow drying of 4-6 hours between recoats. Apply appropriate finishing coat over vertical surfaces within 7 days.

ROLLER

For best results, use a Long Nap Felt Roller.

INFORMATION AND CARE

ENVIRONMENTAL HEALTH AND SAFETY

- Use only with adequate ventilation during application and drying.
- Avoid contact with eyes and prolonged or repeated contact with skin.
- Do not breathe spray mist or sanding dust.
- Use disposable rubber gloves, dust mask or nose pad during application, sanding and clean up.
- Close container after each use.
- Wash thoroughly after handling.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of contact with skin, immediately wash skin with soap and plenty of water. Seek medical attention if irritation develops or persists.
- No added Lead, Mercury, Chromium, Arsenic and other heavy metals.

POST PAINTING CARE

- Apply finishing coat within 7 days of primer application.
- For optimum performance, wash and clean algal and fungal growths over the surface periodically.

PRECAUTION

- Do not apply at temperatures below 10° C. and over 45° C. and humidity greater than 90%.
- Ensure that the terrace surface has adequate slope to avoid water ponding.
- Ensure that Profect WaterStop Basecoat Exteriors is applied at least 6 inches inside the drain pipe
- Ensure proper washing and cleaning of surface to avoid dust accumulation.
- Avoid abuses like movement of heavy equipment or sharp objects on the terrace or anything which can puncture the coating.
- Shake, stir and strain before use.
- In case of contact with eyes, wash with plenty of water. Seek medical advice.
- Tightly close the lid when not in use and store in a cool dry place.

PRODUCT INFORMATION

Colours	White
Drying Time	• Surface Dry – 60 mins • Recoat – 4 hrs
Vehicle Type	Acrylic System
Thin with	Potable Water
VOC levels	Low

The Profect Preparation Products:

INTERIOR & EXTERIOR

JSW Paints Preparation Range offers optimum base for the painting surface so as to ensure that the finishing coats provide a beautiful experience of painting spaces.



PROFECT WALL PUTTY



PROFECT WATERSTOP BASECOAT ONE

JSW Paints Profect Top Coats Range:

Our extensive range of water-based emulsions are designed to capture myriad ideas of beauty and evoke a spectrum of emotions that set the perfect ambience.



MAJESTIC EXTERIORS



REGAL EXTERIORS



ELEGANT EXTERIORS

Version No. 01 (08/2026)
This information sheet supersedes all previous versions.
For feedback/complaints, write to Customer Care Manager, JSW Paint Ltd, Jindal Mansion, 5A, Dr. G. Deshmukh Marg, Mumbai 400 026, India or email at ccpaints@jsw.in or call on 1800-121-5797.

*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.
^Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.