



# Profect

ELEGANT INTERIORS



A specially formulated water-based modified acrylic emulsion with low VOC. It delivers bright colours and unmatched opacity, making your walls look radiant and beautiful for years to come.

It is powered with unique Anti-Chalking properties, it prevents the paint film from chalking due to environmental elements.



20 L

## PACK SIZES

## GLOSS LEVEL



### FEATURES



- Bright Finish
- 4 Years Warranty\*
- Low VOC
- Water Based
- Modified Acrylic

### SURFACES



For new or previously painted walls, plastered and prepared masonry surfaces. Ideal for surfaces where good durability and superior coverage is desired, with a bright finish.

### CAUTION



- Do not apply if temperature is below 10°C or above 45°C.
- Do not apply if humidity is greater than 90%.
- Do not over-thin paint. Use thinned paint within 24 hours.
- Shake, stir and strain the paint before use.
- In case of contact with eyes, wash with plenty of water.
- Tightly close the lid when not in use and store in a cool and dry place.



## PREPARATION

- Surfaces to be painted must be clean, dry, and free from seepage, leakage, loose old paint, dirt, dust, grease, oil, soap, wax and other impurities.
- Remove any peeling paint and sand these areas to feather edges smooth with adjacent surfaces.
- New plaster or masonry surfaces must be allowed to cure (28 days) before application.
- Cured plaster should be hard (non-powdery) and in sound condition.
- Growths of fungus, algae or moss should be removed by wire brushing and washing thoroughly with potable water.
- In case of areas having excess dampness, please repair the surface before applying paint.
- In case there are structural cracks, please study and repair them with a structural engineer.
- Open non-structural cracks in a V-groove and fill with cement/crack filler. Prime the entire surface with JSW Paints Profect Primer Interior.
- Apply cement/acrylic putty (wherever needed) to fill the dents and level the surface.
- Sand and smoothen the surface with sandpaper no. 320 and wipe it clean before paint application.



## APPLICATION

- Apply one coat of JSW Paints Profect Primer Interior over entire surface.
- Allow primer to dry for 3-4 hours before finish coat.
- Smoothen the surface with sandpaper no. 320 and wipe it clean.
- Dilute paint with 50-60% potable water and apply two coats with Short Nap Felt Roller, at an interval of 3-4 hours over properly prepared bare or painted interior surfaces.
- Dark shades may require additional finish coats.



## INFORMATION AND CARE

### HEALTH, SAFETY, SECURITY AND ENVIRONMENT

- Use only with adequate ventilation during application and drying.
- Avoid contact with eyes and prolonged or repeated contact with skin.
- Do not inhale the spray mist or sanding dust.
- Use a dust mask or nose pad during application, sanding and clean-up process.
- Close the container after each use and store in a cool and dry place, in an upright position.
- Keep out of reach of children and away from edible items.
- Do not use empty containers as means to store food.
- Seek immediate medical attention if paint is ingested or swallowed by mistake.
- Wash skin thoroughly after handling.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of contact with skin, immediately wash with soap and plenty of water. Seek medical attention if irritation develops or persists.
- Do not pour paint waste in water courses or in common waste. Needs to be recycled or disposed as per hazardous waste management rules.
- No added Lead, Mercury, Chromium, Arsenic or any other heavy metals.

### POST PAINTING CARE

- Prevent sharp objects, or impact that may damage the paint film.
- Ensure proper cleaning of surface at an interval of every 6 months.

## PRODUCT INFORMATION

Tint Bases

PEI 1

### KEY DATA

No. of colours

900+ shades  
(Ask for Colourvista Shade  
Panorama Fan deck)

Coverage<sup>^</sup>

100 - 110 sq.ft./L/2coats  
9.29 - 10.2 m<sup>2</sup>/L/2coats

Drying Time\*  
(30°C @ 60 R/H)

Surface Dry - 30 minutes  
Recoat - 4 hours

Flash Point

N/A

Sheen Level

2 - 5 units @ 60° GH

Vehicle Type

Modified Acrylic

Thin with

Clean Water (upto 50 - 60%)

VOC levels~

Low

## Other Pröfect Products:



REGAL INTERIORS



REGAL EXTERIORS



MAJESTIC EXTERIORS



ELEGANT EXTERIORS



JSW Paints presents Colourvista Shade **Panorama**, a splendid collection of 1808 curated shades assembled in tones for every mood. The Colourvista Shade **Panorama** Fandeck enables you to easily pick the right colour and choose colour combinations for your projects.



Colourvista Shade Panorama

### FEATURES OF THE INNOVATIVE FANDECK

- 1808 Curated Shades
- Tone Based User-friendly Fandeck
- Easy to Choose Colour Combinations

Version No. 02 (04/2026)

This information sheet supersedes all previous versions

For feedback/complaints, write to Customer Care Manager, JSW Paint Ltd, Jindal Mansion, 5A, Dr. G.Deshmukh Marg, Mumbai - 400 026, India, or email at ccpaints@jsw.in or call on 1800-121-5797.

\*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.

<sup>^</sup>Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.