



Profect

ELEGANT EXTERIORS SILK



JSW Paints Profect Elegant Exteriors Silk is a durable, water-based modified acrylic emulsion with soft sheen for exterior surfaces with weather protection qualities, that makes it dependable across seasons and resists colour fading. The microporous film allows consistent performance properties throughout all seasons. Its unique polymer film provides good hiding, and its 'Extra Coverage Formula' covers a larger area in the same quantity of paint.

PACK SIZES



20 L

GLOSS LEVEL



MATT



SILK



SATIN



GLOSS

FEATURES



Protection For Exterior

Bright Finish

4 Years Warranty*

Low Voc

Water Based

Modified Acrylic

SURFACES



For new or previously painted walls, plastered and prepared masonry surfaces.

Ideal for surfaces where good durability and superior coverage is desired with a bright finish.

CAUTION



Do not apply below 10 °C or above 45 °C.

Do not apply if humidity is more than 90%.

Do not over-thin. Use thinned paint within 24 hours.

Shake, stir and strain the paint before use.

In case of contact with eye, wash with plenty of water.

Tightly close the lid when not in use and store in a cool and dry place.



PREPARATION

- Surfaces to be painted must be clean, dry and free from seepage, leakage, loose old paint, dirt, dust, grease, oil, soap, wax and other impurities.
- Remove any peeling paint and sand these areas to feather edges smooth with adjacent surfaces.
- New plaster or masonry surfaces must be allowed to cure for 28 days before application.
- Cured plaster should be hard (non-powdery) and in sound condition.
- Growths of fungus, algae or moss should be removed by wire brushing and washing thoroughly with potable water.
- In case of areas having excess dampness, please repair the surface before painting.
- In case there are structural cracks, please study and repair them with a structural engineer.
- Open non-structural cracks in a V-groove and fill with cement/crack filler.
- Apply cement/acrylic putty wherever needed to fill the dents and level the surface.
- Wipe it clean before painting application.



APPLICATION

- Apply one coat of JSW Paints Profect Primer Exterior over the entire surface.
- Allow primer to dry for 3-4 hours before applying the finish coat.
- Dilute paint with 50-60% potable water and apply 2 coats with Long Nap Felt Roller, at an interval of 3-4 hours over properly prepared, bare or painted exterior surfaces.
- Dark shades may require additional finish coats.



INFORMATION AND CARE

ENVIRONMENTAL HEALTH AND SAFETY:

- Use only with adequate ventilation during application and drying.
- Avoid contact with eyes and prolonged or repeated contact with skin.
- Do not breathe spray mist or sanding dust.
- Use dust mask or nose pad during application, sanding and cleaning up.
- Close container after each use.
- Wash thoroughly after handling.
- In case of contact with eyes, rinse your eyes immediately with plenty of water and seek medical advice.
- In case of contact with skin, immediately wash skin with soap and plenty of water. Seek medical attention if irritation develops or persists.
- No added Lead, Mercury, Chromium, Arsenic and other heavy metals.

POST PAINTING CARE

- For the best performance of paints, ensure proper washing and cleaning of all algal and fungal growth if any, at regular intervals of 6 months.

PRODUCT INFORMATION

Tint Base	PEES 1, 2
No. of colours	1100+ shades (Ask for Colourvista Shade Panorama fan deck)
Coverage*	55-65 sq.ft./L/2 coats 5.11-6.03 m ² /L/2 coats
Drying Time @ 30°C & R.H 65%	Surface Dry - 30 minutes Recoat - 4 hours
Sheen (@60° Gloss Head)	7 - 10 units @ 60° GH
Vehicle Type	Modified Acrylic
VOC Level	Low
Flash Point	N/A

Other Prôfect Products:



REGAL INTERIORS



REGAL EXTERIORS



ELEGANT INTERIORS



MAJESTIC EXTERIORS



JSW Paints presents Colourvista Shade **Panorama**, a splendid collection of 1808 curated shades assembled in tones for every mood. The Colourvista Shade **Panorama** Fandeck enables you to easily pick the right colour and choose colour combinations for your projects.



Colourvista Shade Panorama

FEATURES OF THE INNOVATIVE FANDECK

- 1808 Curated Shades
- Tone Based User-friendly Fan deck
- Easy to Choose Colour Combinations

Version No. 02 (04/2026)

This information sheet supersedes all previous versions.

For feedback/complaints, write to Customer Care Manager, JSW Paint Ltd, Jindal Mansion, 5A, Dr. G.Deshmukh Marg, Mumbai 400 026, India or email at ccpaints@jsw.in or call on 1800-121-5797.

*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.

^Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.