



Profect

ELEGANT INTERIORS SILK



JSW Paints Profect Elegant Interiors Silk is a specially formulated, water-based modified acrylic emulsion with Low VOC. It delivers a soft sheen, bright colours and unmatched opacity, making your walls look radiant and beautiful for years to come. It is powered with unique Anti-Chalking properties, it prevents the paint film from chalking due to environmental elements.



20 L

PACK SIZES

GLOSS LEVEL



FEATURES

- Bright Finish
- 4 Years Warranty*
- Low VOC
- Water Based
- Modified Acrylic

SURFACES

For new or previously painted walls as well as plastered and prepared masonry surfaces.

Ideal for surfaces where good durability, superior coverage, and a bright finish are desired.

CAUTION

- Do not apply below 10° C or above 45° C.
- Do not apply if humidity is more than 90%.
- Do not over-thin. Use thinned paint within 24 hours.
- Shake, stir and strain paint before use.
- In case of contact with eyes, wash with plenty of water.
- Tightly close the lid when not in use and store in a cool and dry place.



PREPARATION

- Surfaces to be painted must be clean, dry and free from seepage, leakage, loose old paint, dirt, dust, grease, oil, soap, wax and other impurities.
- Remove any peeling paint and sand these areas to feather edges smooth with adjacent surfaces.
- New plaster or masonry surfaces must be allowed to cure 28 days before application.
- Cured plaster should be hard (non-powdery) and in sound condition.
- Growths of fungus, algae or moss should be removed by wire brushing and washing thoroughly with potable water.
- In case of areas having excess dampness, please repair the surface before painting.
- In case there are structural cracks, please study and repair them with a structural engineer.
- Open non-structural cracks in a V-groove and fill with cement/crack filler.
- Apply cement/acrylic putty wherever needed to fill the dents and level the surface.
- Sand and smoothen the surface with sandpaper No. 320 and wipe it clean before the paint application.



APPLICATION

- Apply one coat of JSW Paints Profect Primer Interior over the entire surface.
- Allow primer to dry for 3-4 hours before applying the finish coat.
- Dilute paint with 50-60% potable water and apply 2 coats with Short Nap Felt Roller, at an interval of 3-4 hours over properly prepared, bare or painted interior surfaces.
- Dark shades may require additional finish coats.



INFORMATION AND CARE

ENVIRONMENTAL HEALTH AND SAFETY:

- Use only with adequate ventilation during application and drying.
- Avoid contact with eyes and prolonged or repeated contact with skin.
- Do not breathe spray mist or sanding dust.
- Use dust mask or nose pad during application, sanding and cleaning up.
- Close container after each use.
- Wash thoroughly after handling.
- In case of contact with eyes, rinse your eyes immediately with plenty of water and seek medical advice.
- In case of contact with skin, immediately wash skin with soap and plenty of water. Seek medical attention if irritation develops or persists.
- No added Lead, Mercury, Chromium, Arsenic and other heavy metals.

POST PAINTING CARE

- For the best performance of paints, ensure proper washing and cleaning of all algal and fungal growth if any, at regular intervals of 6 months.

PRODUCT INFORMATION

Tint Base	PEIS 1
No. of colours	900+ shades (Ask for Colourvista Shade Panorama Fan deck)
Coverage*	100 - 110 sq.ft./L/2 coats 9.29 - 10.2 m ² /L/2coats
Drying Time @ 30°C & R.H 65%	Surface Dry - 30 minutes Recoat - 4 hours
Sheen (@60° Gloss Head)	7 - 10 units @ 60° GH
Vehicle Type	Modified Acrylic
VOC Level	Low
Flash Point	N/A

Other Prôfect Products:



REGAL INTERIORS



REGAL EXTERIORS



ELEGANT INTERIORS



MAJESTIC EXTERIORS



JSW Paints presents Colourvista Shade **Panorama**, a splendid collection of 1808 curated shades assembled in tones for every mood. The Colourvista Shade **Panorama** Fandeck enables you to easily pick the right colour and choose colour combinations for your projects.



Colourvista Shade Panorama

FEATURES OF THE INNOVATIVE FANDECK

- 1808 Curated Shades
- Tone Based User-friendly Fan deck
- Easy to Choose Colour Combinations

Version No. 02 (04/2026)

This information sheet supersedes all previous versions.

For feedback/complaints, write to Customer Care Manager, JSW Paint Ltd, Jindal Mansion, 5A, Dr. G.Deshmukh Marg, Mumbai 400 026, India or email at ccpaints@jsw.in or call on 1800-121-5797.

*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.

^Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.