



# Profect

## Waterstop Basecoat One

EXTERIORS



JSW Paints Profect Waterstop Basecoat One is a single-coat waterproofing basecoat designed for use with all JSW Paints Exterior Emulsions on vertical walls. Offering excellent waterproofing capabilities with unmatched whiteness and opacity. It is a thoughtfully engineered fibre-reinforced elastomeric waterproof coating. JSW Paints Profect Waterstop Basecoat One is designed with special elastomeric and tough acrylic polymers, as well as fibre reinforcement to give long-lasting waterproofing.

*Tested to protect the structures from moisture and dampness.*

#### PACK SIZES



20 L

#### GLOSS LEVEL



#### FEATURES



- 6 years of endurance for exterior waterproofing. Prevents water seepage by acting as a protective layer against rain for the substrate.
- Waterproofing: Best-in-class waterproofing of 6 bars with positive hydrostatic pressure on vertical walls.
- High mechanical strength, fiber-reinforced film which creates a tougher and thicker film for application on exterior walls.
- Improves the top coat performance.
- Anti-carbonation: Increases the life of a concrete surface.
- Elongation: 150 +/- 10% Vertical Surfaces.
- One coat waterproofing.

#### CERTIFICATION



**Hydrostatic Pressure:**  
**Water Permeability:**  
EN 12390-8:2019,  
passes up to 6 bars of  
positive water pressure.



#### PREPARATION

- Newly plastered surfaces to be cured for 28 days. Do not apply on bituminous, asphalt, porous cement, ash brick, ceramic tiles or glossy substrate.
- All surfaces to be painted should be free from loose paint, powders, dust, dirt, rust, oil, wax, grease, laitance, other contaminants, fungus, algae, leakage, seepage, efflorescence and structural cracks/defects.
- Study structural cracks if any with a structural engineer and repair.
- Open non-structural cracks in a V shaped grooves and fill with JSW Paints iBlok WaterStop Crack Fix for superior performance (For More Details Please refer PIS).
- Ensure the surface should be in SSD condition before application.



#### APPLICATION

- Apply a single coat of JSW Paints Profect Waterstop Basecoat One (without dilution) to the prepared surface with a roller or brush, achieving a coverage of 35-40 sq ft/L at forced coverage.
- Allow it to dry for 4 to 6 hours.
- Post drying, apply the 2nd coat of recommended JSW Exterior Top Coat.
- For better results, use only the JSW Paints Emulsions range at standard dilution.



## PRECAUTIONS & CARE

- Apply at temperatures between 10°C & 45°C and humidity less than 90% RH.
- This is a direct application product, dilution is not required.
- Shake and stir before use.
- In case of contact with eyes, wash with plenty of water. Seek medical advice.
- Tightly close the lid when not in use and store in a cool, dry place.
- Avoid actions like moving of heavy equipment or sharp objects on the terrace or anything which can puncture the coating.
- Do not apply during rains or when it is expected to rain.
- Before application, mix the material with a mechanical mixer to get a homogeneous and rollable/brushable consistency.

## BRUSH

For best results, use the long nap felt roller.

## DILUTION

Dilution by water is not required. Apply directly on an exterior wall surface by using a brush or a roller.

## PRODUCT INFORMATION

Colours | White

### KEY DATA

Coverage <sup>^</sup>	35 to 40 Sq.Ft./Litre one coat
Drying Time	Surface dry – 40 min. Top coat application – 4-6 hrs.
Sheen Level	NA
Vehicle Type	Emulsion
Thin with	No dilution

## POST PAINTING CARE

- Apply finishing coat within 7 days of Base Coat application.
- For optimum performance, wash and clean algal and fungal growths over the surface periodically.

## The Prōfect Preparation Products:

Prōfect Preparation Range offers optimum base for the painting surface. So as to ensure that the finishing coats provide a beautiful experience of painting spaces.



PROFECT WALL PUTTY



WALL PRIMER ECO EXTERIORS



WALL PRIMER ECO INTERIORS



WALL PRIMER EXTERIORS



WALL PRIMER INTERIORS



TEXTURE

## JSW Paints Prōfect Top Coats Range:

Our extensive range of water-based emulsions are designed to capture myriad ideas of beauty and evoke a spectrum of emotions that set the perfect ambience.



MAJESTIC EXTERIORS



REGAL INTERIORS



REGAL EXTERIORS



ELEGANT INTERIORS



ELEGANT EXTERIORS



CLASSIC INTERIORS

JSW Paints - Everything about the paint, its application and finish is designed to be the 'Simple-Swift-Sure' way to making homes beautiful.

Version No. 02 (04/2026.)

This information sheet supersedes all previous versions.

For feedback/complaints, write to Customer Care Manager, JSW Paint Ltd, Jindal Mansion, 5A, Dr. G. Deshmukh Marg, Mumbai 400 026, India or email at [ccpaints@jsw.in](mailto:ccpaints@jsw.in) or call on 1800-121-5797.

<sup>\*</sup>Subject to compliance with conditions maintained in Product Information Sheet, regional climatic conditions, accidental damage, usual wear and tear in the area where applied.

<sup>^</sup>Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.

<sup>^</sup>Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.

-VOC Levels as certified by NTH. Meets VOC as per BIS Standard – IS 101 (Part 2/Sec 2)/1986 & IS 101 (Part 2/Sec 1)/1988.