



Pròfect

SYNTHETIC ENAMEL
Gloss



Pròfect Synthetic Enamel Gloss is designed to provide a high gloss coating over wood, metal and masonry surfaces.

PACK SIZES



20 L

GLOSS LEVEL



FEATURES



FOR WOOD AND METAL



GLOSSY FINISH



EASE OF APPLICATION



NO ADDED LEAD & OTHER HEAVY METALS



DURABLE FINISH



EXCELLENT ADHESION

CAUTION



Do not over-thin. Filter the diluted paint material before spraying to ensure applied coating is free from contamination and should be used within 24 hrs.

Do not apply at temperatures below 10°C & over 45°C.

Do not dilute above recommendation and use within 24 hours post dilution.

Shake, stir and strain paint before use.

Maintain air ventilation for quick drying.

Tightly close the lid when not in use. Store in an upright position in a cool dry place.



PREPARATION

- Ensure wood is aged properly. For pre-painted wood, scrape off loose paint.
- Smoothen with emery paper no. 320. Wipe it clean.
- Ensure metal surface is free from dirt, oil, grease, rust or any contamination.
- For welded joints, ensure sharp edges/pikes are smoothened with machine tool.
- Remove loose rust and old loose paint by metal wire brushing.
- Sand with emery paper no. 180 and wipe clean.



APPLICATION

SURFACES Wood, Metal and Masonry Surfaces

TOOLS Brush or Roller as required

DILUTION 8-10% by volume with mineral turpentine oil

Application Process:

STEP	NO. OF COATS	PRODUCT	RECOAT TIME
STEP 1	Sand and smoothen with emery paper no. 320. Wipe clean		
STEP 2	Wood and Masonry Surface	Pròfect Acrylic Putty, Pròfect Wall Putty	6-8hrs
STEP 3	Wood, Metal and Masonry Surface	Pròfect Wood Primer, Pròfect Metal Primer and Pròfect Wall Primer (Dilution: 5-10% by volume with mineral turpentine oil)	6-8hrs
STEP 4	Sand and smoothen with emery paper no. 320. Wipe clean		
STEP 5	First Coat	Pròfect SYNTHETIC ENAMEL Gloss	8hrs
STEP 6	Second Coat	Pròfect SYNTHETIC ENAMEL Gloss	8hrs



INFORMATION AND CARE

ENVIRONMENTAL HEALTH AND SAFETY

- Store the product under ambient conditions in well-ventilated locations and away from sources of ignition and fire.
- Keep out of reach of children and away from eatables.
- May be harmful if swallowed. In case of ingestion, seek immediate medical attention.
- Wear eye protection during application. In case of contact with eyes rinse immediately with plenty of water and seek medical advice.
- In case of skin contact, immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
- Do not pour left-over paint down the drain or in water sources .
- In the event of spills, contain spillage using sand or earth.
- No added Lead, Mercury or Chromium compound.

POST PAINTING CARE

- For removing stains on tiles and metal surfaces, apply NC Thinner on the surface and wipe clean.
- Prevent sharp objects or impacts that damage the paint film.
- Ensure proper cleaning of the surface at an interval of 6 months.

PRODUCT INFORMATION

Gloss level	85 +/- 5 @ 60°GH
Coverage	90 - 110 sq.ft./L/2 coats
Drying time - Surface Dry (30°C @ 60°GH)	1hr
Drying time - Recoat (30°C @ 60°GH)	8hr
Flash point	>30°C
Vehicle type	Alkyd
Shelf life	36 months
Direct Shades	White, Black, Golden Yellow, Smoke Grey

The Prōfect Preparation Products:

Prōfect Preparation Range offers optimum base for the painting surface. So as to ensure that the finishing coats provide a beautiful experience of painting spaces.



PROFECT WALL PUTTY



WALL PRIMER ECO EXTERIORS



WALL PRIMER ECO INTERIORS



WALL PRIMER EXTERIORS



WALL PRIMER INTERIORS



TEXTURE

JSW Paints Prōfect Top Coats Range:

Our extensive range of water-based emulsions are designed to capture myriad ideas of beauty and evoke a spectrum of emotions that set the perfect ambience.



MAJESTIC EXTERIORS



REGAL INTERIORS



REGAL EXTERIORS



ELEGANT INTERIORS



ELEGANT EXTERIORS



CLASSIC INTERIORS

Version No. 01 (04/2024.)

This information sheet supersedes all previous versions

For feedback/complaints, write to Customer Care Manager, JSW Paint Pvt. Ltd, Jindal Mansion, 5A, Dr. G. Deshmukh Marg, Mumbai 400 026, India or email at ccpaints@jsw.in or call on 1800-121-5797.

*Subject to compliance with conditions maintained in Product Information Sheet, regional climatic conditions, accidental damage, usual wear and tear in the area where applied.

*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.

^Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.

-VOC Levels as certified by NTH. Meets VOC as per BIS Standard - IS 101 (Part 2/Sec 2)/1986 & IS 101 (Part 2/Sec 1)/1988