



# Texture

TOUGH EXTERIORS



JSW PAINTS TEXTURE - TOUGH EXTERIORS 2.5 mm is a textured finish formulated with high quality exterior durable acrylic modified resin and reinforced with quartz sand. It is especially designed as an intermediate coating to make your walls look aesthetically beautiful through a range of engraved finishes. It is a completely environment-friendly product with low VOC levels.

JSW PAINTS TEXTURE is resistant to water and offers excellent protection against humidity, rain and variable climates, thereby ensuring long term protection of your walls.



Pack Size : 30 KG

## FEATURES



ALL-WEATHER DURABILITY



HIGH BONDING



HIDES CRACKS



PLASTER PROTECTION



LOW MAINTENANCE



RELEASES TRAPPED MOISTURE



ANTI-ALGAL PROPERTY



## PREPARATION

- Surfaces to be painted must be clean, dry and free from seepage, leakage, loose old paint, dirt, dust, grease, oil, soap, wax and any other contamination
- Remove any loose paint and sand these areas to feather edges smooth with adjacent surfaces
- New plaster or masonry surfaces must be allowed to cure (28 days) before application
- Cured plaster should be hard (non-powdery) and in sound condition
- Growth of fungus, algae or moss should be removed by wire brushing and washing thoroughly with potable water
- In case of areas having excess dampness/waterproofing issues, please repair the surface before painting
- In case there are structural cracks, please study and repair them with a structural engineer
- Open non-structural cracks in V-groove and fill with cement/crack filler
- Apply JSW Paints Wall Putty (where needed) to fill the dents or to level the surface
- JSW Paints Texture should not be applied on surfaces/substrates that are subjected to continuous seepage or dampness
- For repainting masonry surfaces, Wall Primer application is needed before Texture application



## APPLICATION

- SUBSTRATE** New masonry surfaces or well prepared repainting surface
- TOOLS** For best results, use good quality trowel
- DILUTION** Not Recommended
- PRE-WET** Pre-wet the surface before Texture application


## APPLICATION PROCESS

STEP 1	1 COAT	Wall Primer Pröfect wall Primer	3-4 hrs drying
STEP 2	1 COAT	TEXTURE Finish	12-16 hrs drying
STEP 3	2-3 COATS	HALO / AURUS / PIXA / PROTECT Exteriors	4 hrs drying


## FINISH



HORIZONTAL SCRATCH



RAINFALL



VERTICAL SCRATCH



CRISS CROSS



## INFORMATION AND CARE

### ENVIRONMENTAL HEALTH AND SAFETY

- Use only with adequate ventilation during application and drying
- Avoid contact with eyes and prolonged or repeated contact with skin
- Do not breathe spray mist or sanding dust
- Use disposable rubber hand gloves, dust mask or nose pad during application, sanding and clean up
- Wash thoroughly after handling
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
- In case of skin contact, immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists
- No added Lead, Mercury, Chromium, Arsenic or other heavy metals

### PRECAUTION

- Do not apply below 10° C or above 45° C or if humidity is > 90%
- Pre-wet the surface before application of Texture
- Tightly close the bag when not in use and store in a cool, dry place
- Use of Universal Stainers or colourants is not recommended
- Thinning is not advisable
- Open bag needs to be used within 24 hours

## PRODUCT INFORMATION

Colour | White

### KEY DATA

#### Coverage<sup>^</sup>

(On a normal masonry surface by a roller to obtain an even coating of ~2.5mm)

2 - 2.5 sq.ft/kg/coat

0.19 - 0.23 sq.m/kg/coat

#### Drying Time\*

(30°C @ 60 R/H)

Surface Dry - 30-60 minutes

Drying Time - 12 - 16 hours

#### Flash Point

N/A

#### Sheen Level

N/A

#### Binder Type

Acrylic Modified Resin

#### Thin With

Not recommended

#### VOC levels~

<20 gms/kg

## Our product range:



### JSW Paints Preparatory Products Range:

Our product range offers optimum base for the painting surface so as to ensure that the finishing coats provide a beautiful experience of painting spaces.

### JSW Paints Top Coat Range:

Our extensive range of water-based emulsions are designed to capture myriad ideas of beauty and evoke a spectrum of emotions that set the perfect ambience.



WALL PRIMER EXTERIORS



HALO EXTERIORS



AURUS EXTERIORS



PIXA EXTERIORS



PROFECT WALL PRIMER EXTERIORS



REGAL EXTERIORS



ELEGANT EXTERIORS



MAJESTIC EXTERIORS

Version No. 02 (12/2023).

This information sheet supersedes all previous versions

For feedback/complaints, write to Customer Care Manager, JSW Paints Pvt. Ltd., Jindal Mansion, 5A, Dr. G. Deshmukh Marg, Mumbai 400 026, India or email at [ccpaints@jsw.in](mailto:ccpaints@jsw.in) or call on 1800-121-5797.

\*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.

<sup>^</sup>Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.

~Applied for VOC levels certification by NTH.