



Texture

TOUGH EXTERIORS 1.5 MM



JSW Paints Texture – Tough Exteriors 1.5 mm is a high-performance textured exterior finish made with durable, acrylic-modified resin and reinforced quartz sand. Designed as an intermediate coating, it enhances the beauty of your walls with a wide range of elegant, engraved textures.

Built for the outdoors, it offers strong resistance to water and delivers reliable protection against humidity, rain, and changing climates, keeping your walls protected for the long run. It's also environmentally responsible, with low VOC levels for a safer, cleaner finish.



Pack Size : 30 KG

FEATURES



ALL WEATHER DURABILITY



LOW VOC



HIGH BONDING



HIDES CRACKS



PLASTER PROTECTION



LOW MAINTENANCE



RELEASES TRAPPED MOISTURE



ANTI-ALGAL PROPERTY



UV RESISTANT



PREPARATION

- Surfaces to be painted must be clean, dry and free from seepage, leakage, loose old paint, dirt, dust, grease, oil, soap, wax and any other contaminations.
- Remove any loose paint and sand these areas to feather edges smooth with adjacent surfaces.
- New plaster or masonry surfaces must be allowed to cure (28 days) before application.
- Cured plaster should be hard (non-powdery) and in sound condition.
- Growth of fungus, algae or moss should be removed by wire brushing and washing thoroughly with potable water.
- In case of areas having excess dampness/waterproofing issues, please repair the surface before painting.
- In case there are structural cracks, please study and repair them with a structural engineer.
- Open non-structural cracks in a V-groove and fill with cement/crack filler.
- Apply JSW Paints Wall Putty (where needed) to fill the dents or to level the surface.
- JSW Paints Texture should not be applied on surfaces/substrates that are subjected to continuous seepage or dampness.
- For repainting masonry surfaces, Wall Primer application is needed before Texture application



APPLICATION

- SUBSTRATE** New masonry surfaces or well-prepared repainting surface
- TOOLS** For best results, use good quality trowel
- DILUTION** Not recommended
- PRE-WET** Pre-wet the surface before texture application

APPLICATION PROCESS


STEP 1 (Optional)	1 COAT	Wall Primer Prōfect Wall Primer (or)	3-4 hrs drying
STEP 2	1 COAT	TEXTURE Finish	12-16 hrs drying
STEP 3	2-3 COATS	HALO / AURUS / PROFECT REGAL / PROFECT MAJESTIC Exteriors	4 hrs drying

Application of Primer is mandatory only for Re-painting surfaces.

FINISH



HORIZONTAL SCRATCH



RAINFALL



VERTICAL SCRATCH



CRISS CROSS



INFORMATION AND CARE

ENVIRONMENTAL HEALTH AND SAFETY

- Use only with adequate ventilation during application and drying.
- Avoid contact with eyes and prolonged or repeated contact with skin.
- Do not breathe spray mist or sanding dust.
- Use disposable rubber hand gloves, dust mask or nose pad during application, sanding and clean up.
- Wash thoroughly after handling.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of contact with skin, immediately wash skin with soap and plenty of water. Seek medical attention if irritation develops or persists.
- No added Lead, Mercury, Chromium, Arsenic or other heavy metals.

PRECAUTION

- Do not apply below 10° C or above 45° C or if humidity is > 90%.
- Pre-wet the surface before application of Texture.
- Tightly close the bag when not in use and store in a cool, dry place.
- Use of Universal Stainers or colourants is not recommended.
- Thinning is not advisable.
- Open bag needs to be used within 24 hours.

PRODUCT INFORMATION

Colour

White

KEY DATA

Coverage[^]

(On a normal masonry surface by a roller to obtain an even coating of ~2mm)

2.9 - 3.4 sq.ft/kg/coat

Drying Time* (30°C @ 60 R/H)

Surface Dry - 30-60 minutes
Drying Time - 12 - 16 hours

Flash Point

N/A

Sheen Level

N/A

Binder Type

Acrylic Modified Resin

Thin With

Not recommended

VOC levels~

<20 gms/kg

Our product range:



JSW Paints Preparatory Products Range:

Our product range offers optimum base for the painting surface so as to ensure that the finishing coats provide a beautiful experience of painting spaces.

JSW Paints Top Coat Range:

Our extensive range of water-based emulsions are designed to capture myriad ideas of beauty and evoke a spectrum of emotions that set the perfect ambience.



WALL PRIMER EXTERIORS



HALO EXTERIORS



AURUS EXTERIORS



PIXIA EXTERIORS



PRØFACT WALL PRIMER EXTERIORS



REGAL EXTERIORS



ELEGANT EXTERIORS



PRØFACT MAJESTIC EXTERIORS

Version No. 03 (05/2026).

This information sheet supersedes all previous versions

For feedback/complaints, write to JSW Paints Ltd., Jindal Mansion, Dr. G. Deshmukh Marg, Mumbai 400 026, Maharashtra, India or email at ccpaints@jsw.in or call on 1800-121-5797.

*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.

[^]Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.

~Applied for VOC levels certification by NTH. The product name does not represent the thickness or stone size of the product.